



**PORSCHE**



# **Service Information Technik**

**718 Boxster/S**  
**Model Year 2017 (982)**

This brochure does not replace the Porsche repair manuals.

Dimensions and tolerances can be found in the documents in the PIWIS information system.

## Foreword

## 718 Boxster/S Model Year 2017 (982)

The new 718 Boxster. The future: Open as always.

“Roadster dreams have always borne the name Porsche.” With its new name “718 Boxster”, the Boxster therefore continues the tradition of successful, fast and lightweight 2-seater roadsters.

Its renowned ancestors, the 550 Spyder and 718, already enjoyed great motor sports successes and produced corresponding headlines with the concept of an agile cornering specialist powered by a legendary flat-four engine. The lightweight engine in particular resulted in an ideal weight distribution with a central and low centre of gravity, thus making it possible to realise the driving dynamics that allowed the 718 to achieve numerous successes in the 50s and 60s.

The new generation of the Boxster now follows in these footsteps, loosely based on the maxim “Less is more”.

The heart of the roadster, which has been uncompromisingly designed for maximum agility and driving dynamics, is the completely newly developed turbo flat-four engine generation.

Offering compact design together with optimum efficiency, the new engines with a displacement of 2.0 and 2.5 l represent a quantum leap in performance for the Boxster also in combination with the introduction of turbocharging.

The fundamental performance capability of the four-cylinder technology was also confirmed in 2015 by the victory of the 919 Hybrid at Le Mans – with a state-of-the-art turbocharged 4-cylinder engine concept.

The Boxster adopts this successful concept and transfers it to series production with the 718 Boxster models. The new flat-four turbo engine combines a high-revving layout with enormous torque, while at the same time offering a highly emotional engine sound with typical flat engine characteristics.

However, most important of all: 35 hp extra engine power and up to 100 Nm more torque combined with significantly reduced emissions are clear proof of the performance capability of this drive concept.

## **718 Boxster/S**

### **Model Year 2017 (982)**

The 718 Boxster S additionally uses the variable turbine geometry (VTG) familiar from the 911 Turbo and underlines the significantly enhanced performance with acceleration from 0-100 km/h in just 4.2 s.

In addition to the convincing drive concept, the new 718 Boxster also features a new, much more distinctive design in comparison with the predecessor, an even sportier chassis and suspension setup with 10% more direct steering, as well as a host of new performance, comfort and assistance systems.

With the introduction of the new infotainment system, comprising PCM, Connect or Connect Plus, a state-of-the-art and comprehensive connectivity package is now also available in the 718 Boxster. This consists of completely new, high-performance hardware with a high-resolution 7-inch multi-touch screen. This provides the basis for a modern user interface like that familiar from smartphones. This is also additional impressive proof of the future-oriented technologies used in a vehicle that, like its ancestors, will set new standards in the class of lightweight and powerful roadsters.

You can therefore look forward to the new Porsche 718 Boxster. Its technological enhancements are described in detail in this Service Information Technik manual.

Your Global Service Qualification Team







## Contents

### 1 Engine

- 1.1 Introduction
- 1.2 2.0 l/2.5 l flat-four engine with turbocharger

### 2 DME engine electronics

- 2.1 Introduction
- 2.2 2.0 l/2.5 l flat-four engine with turbocharger

### 3 Power transmission

- 3.1 Introduction
- 3.2 Technical data
- 3.3 Manual transmission
- 3.4 Porsche Doppelkupplung (PDK)
- 3.5 Transmission mount

### 4 Chassis

- 4.1 Introduction
- 4.2 Front axle
- 4.3 Rear axle
- 4.4 Power steering
- 4.5 Tyre Pressure Monitoring (TPM)
- 4.6 Wheels and tyres
- 4.7 Brakes
- 4.8 Control systems

### 5 Body

- 5.1 Introduction
- 5.2 Comparison of technical data
- 5.3 Box-type bodyshell

## 718 Boxster/S Model Year 2017 (982)

1

1

2

Engine

1

25

25

27

DME engine electronics

2

65

65

65

66

69

72

Power transmission

3

75

75

76

76

77

79

83

84

86

Chassis

4

93

93

93

93

Body

5

# 718 Boxster/S

## Model Year 2017 (982)

Body –  
Exterior equipment

6

## 6 Body – Exterior equipment 103

- 6.1 Introduction 103
- 6.2 Front 104
- 6.3 Side view 106
- 6.4 Rear 110
- 6.5 Roof systems 114

Body –  
Interior equipment

7

## 7 Body – Interior equipment 117

- 7.1 Introduction 117
- 7.2 Trim panels, storage facilities and luggage compartment 118
- 7.3 Operating and display concept 120

Heating and air conditioning

8

## 8 Heating and air conditioning 123

- 8.1 Introduction 123
- 8.2 Control panel 123
- 8.3 Refrigerant circuit 124

Electrics and electronics

9


## 9 Electrics and electronics 131

- 9.1 Introduction 131
- 9.2 Network topology 131
- 9.3 Vehicle electrical system/energy management 134
- 9.4 Lighting 134
- 9.5 Instrument cluster 142
- 9.6 Wash/wipe systems 143
- 9.7 Door handles 143
- 9.8 Porsche Car Connect (PCC) 143
- 9.9 Porsche Vehicle Tracking System Plus (PVTS Plus) 144
- 9.10 Driver assistance systems 146
- 9.11 Era Glonass emergency call system 149
- 9.12 Sport Chrono package 150
- 9.13 PCM 4 152
- 9.14 Sound systems 162
- 9.15 Porsche Connect 164
- 9.16 Abbreviations 169






# Group 1 Engine



# 1 Engine

## 1.1 Introduction





Flat-four engine 718 Boxster S MY17

1\_01\_17

A completely new generation of flat-four engines is used in the 718 Boxster MY17. These engines are part of the current 9A2 engine generation, which made its debut in the Porsche 911 Carrera MY17.

The Porsche tradition has its roots in flat-four engines. The goal was therefore clear right from the start: the unique Porsche genes, such as characteristic engine sound, high revving ability and typical Sports Car performance, had to be reconciled with current environmental requirements such as low fuel consumption and emissions. The result is impressive in every respect. In fact, the performance of the previous six-cylinder generation is even significantly bettered.

## 718 Boxster/S Model Year 2017 (982)



Crankshaft drive for the flat-four engine

1\_02\_17

<b>1.1</b>	<b>Introduction</b>	<b>1</b>
<b>1.2</b>	<b>2.0 l/2.5 l flat-four engine with turbocharger</b>	<b>2</b>
1.2.1	Technical data	2
1.2.2	Belt drive	6
1.2.3	Engine block	8
1.2.4	Cylinder head	13
1.2.5	Timing drive mechanism	15
1.2.6	Oil supply	16
1.2.7	Cooling system	19
1.2.8	Special tools	20

## 718 Boxster/S Model Year 2017 (982)

Engine

1



The 718 Boxster MY17 will be offered on the Chinese market with a reduced-power engine version, 184 kW/250 hp. The power reduction will be realised by means of changed DME maps. The engine type is MA220/MDDPA.

The four-cylinder engine generation is characterised in particular by the following features:

- very high power with broad torque curve
- outstanding responsiveness
- very favourable fuel consumption and emission values
- low weight

### 1.2 2.0 I/2.5 I flat-four engine with turbocharger

#### 1.2.1 Technical data

	Unit	718 Boxster MY17	718 Boxster S MY17
<b>Engine type</b>		MA220/MDDP	MA222/MDDN
<b>Design</b>		Flat engine	
<b>Number of cylinders</b>	i	4	
<b>Valves per cylinder</b>		4	
<b>Turbocharging</b>		Turbocharger	VTG turbocharger
<b>Displacement</b>	cm <sup>3</sup>	1,988	2,497
<b>Bore</b>	mm (in)	91 (3.582)	102 (4.016)
<b>Stroke</b>	mm (in)	76.4 (3.008)	
<b>Compression ratio</b>		9.5:1	
<b>Max. power (EC)</b>	kW (hp)	220 (300)	257 (350)
<b>Max. power (USA)</b>	hp	295	345
at engine speed	rpm	6,500	
<b>Max. torque (EC)</b>	Nm	380	420
<b>Net torque (USA)</b>	lbf ft.	280	310
at engine speed	rpm	1,950 – 4,500	1,900 – 4,500
<b>Max. power output per litre (EC)</b>	kW/l	111	103
<b>Idle speed</b>	rpm	800 +/- 50	
<b>Maximum engine speed</b>	rpm	7,500	
<b>Engine speed limitation through</b>		Electronic throttle and fuel cutoff	
<b>Engine weight</b>	kg	181	187
<b>Oil change quantity with filter</b>	L	5.7	

Extract, data available at copy deadline, subject to change




## Comparison of technical data

### 718 Boxster MY17/Boxster MY12-16


	Unit	718 Boxster MY17	Boxster MY12-16
<b>Engine type</b>		MA220/MDDP	MA122
<b>Design</b>		Flat engine	
<b>Number of cylinders</b>		4	6
<b>Valves per cylinder</b>		4	
<b>Turbocharging</b>		Turbocharger	without
<b>Displacement</b>	cm <sup>3</sup>	1,988	2,706
<b>Bore</b>	mm	91	89
<b>Stroke</b>	mm	76.4	72.5
<b>Compression ratio</b>		9.5:1	12.5:1
<b>Max. power (EC)</b>	kW (hp)	220 (300)	195 (265)
at engine speed	rpm	6,500	6,700
<b>Max. torque (EC)</b>	Nm	380	280
at engine speed	rpm	1,950 – 4,500	4,500 – 6,500
<b>Max. power output per litre (EC)</b>	kW/l	111	72
<b>Idle speed</b>	rpm	800 +/- 50	680 +/- 25
<b>Maximum engine speed</b>	rpm	7,500	7,800
<b>Engine weight</b>	kg	181	199

Extract, data available at copy deadline, subject to change

## 718 Boxster/S Model Year 2017 (982)



## 718 Boxster/S Model Year 2017 (982)



### 718 Boxster S MY17/Boxster S MY12-16


	Unit	718 Boxster S MY17	Boxster S MY12-16
<b>Engine type</b>		MA222/MDDN	MA123
<b>Design</b>		Flat engine	
<b>Number of cylinders</b>		4	6
<b>Valves per cylinder</b>		4	
<b>Turbocharging</b>		VTG turbocharger	without
<b>Displacement</b>	cm <sup>3</sup>	2,497	3,436
<b>Bore</b>	mm	102	97
<b>Stroke</b>	mm	76.4	77.5
<b>Compression ratio</b>		9.5:1	12.5:1
<b>Max. power (EC)</b>	kW (hp)	257 (350)	232 (315)
at engine speed	rpm	6,500	6,700
<b>Max. torque (EC)</b>	Nm	420	360
at engine speed	rpm	1,900 – 4,500	4,500 – 5,800
<b>Max. power output per litre (EC)</b>	kW/l	103	68
<b>Idle speed</b>	rpm	800 +/- 50	680 +/- 25
<b>Max. engine speed</b>	rpm	7,500	7,800
<b>Engine weight</b>	kg	187	198

Extract, data available at copy deadline, subject to change

## 718 Boxster/S Model Year 2017 (982)

### Power/torque diagram


#### Full load curve 718 Boxster MY17, engine type MA220/MDDP



Full load curve 2.0-litre flat engine, engine type MA220/MDDP

1\_03\_17

#### Full load curve 718 Boxster S MY17, engine type MA222/MDDN



Full load curve 2.5-litre flat engine, engine type MA222/MDDN

1\_04\_17




- 1 Torque (Nm)
- 2 Engine power (kW)

## 718 Boxster/S Model Year 2017 (982)

Engine

# 1

### Engine number




Position of engine number

1\_05\_17

The engine number is located on the belt side on the right crankcase half and can be read from below in installed condition.

### 1.2.2 Belt drive



- 1 Belt tensioner bracket
- 2 Deflection roller
- 3 Poly-V-belt
- 4 Vibration damper
- 5 Belt tensioner


Belt drive (2.0 I flat engine)

1\_06\_17

## 718 Boxster/S Model Year 2017 (982)

The design of the belt drive is largely identical to that for the six-cylinder engines. Due to the different vibration behaviour, the 2.5 l engine has a vibration damper with decoupled pulley instead of the conventional vibration damper (see below) and a differently matched belt tensioner is used.

### Vibration damper with decoupled pulley



Vibration damper, 718 Boxster MY17 1\_07\_17 Vibration damper with decoupled pulley, 1\_08\_17  
718 Boxster S MY17

The vibration damper with decoupled pulley on the 718 Boxster S has an additional decoupling element (4) between hub and pulley. This significantly reduces transmission of crankshaft rotational irregularity to the belt drive.

There is a maintenance-free plain bearing (3) between the drive hub and pulley to support the radial load due to the belt tension.

Engine

1

- 1 Flywheel mass
- 2 Flywheel mass decoupling element
- 3 Plain bearing
- 4 Pulley decoupling element  
(with steel inner race)
- 5 Drive hub



For design reasons, the vibration damper with decoupled belt pulley does not have any staking bores for adjustment work on the timing drive mechanism. Please observe the current Workshop Manual for adjustment work!

## 718 Boxster/S Model Year 2017 (982)

Engine

# 1




The heat treatment process comprises the three steps

- homogenisation
- quenching
- artificial ageing

This achieves a higher tensile strength of the cast material.

### 1.2.3 Engine block

#### Crankcase



Crankcase 2.0 l/2.5 l flat-four engine

1\_09\_17

#### Design

The design of the flat-four engines for the 718 Boxster MY17 and 718 Boxster S MY17 was derived from the redesigned flat-six engines of the 911 Carrera MY17. By keeping the same parameters (flange dimensions, etc.) relevant for production, the four-cylinder engines can be manufactured on the same production installations as the six-cylinder engines.


The hypoeutectic aluminium alloy AlSi7Cu0.5Mg is used for the crankcase. Production takes place using a low-pressure casting process with subsequent heat treatment.

The procedures for disassembly and assembly of the two crankcase halves and the crankshaft drive essentially correspond to those for the six-cylinder engines.

## Cylinder liners


The fuel consumption and emission characteristics of the engine are positively influenced by an innovative coating for the cylinder liners. This coating technology (PTWA = **P**lasma **T**ransfer **W**ire **A**rc) leads to a significant reduction in the internal engine friction. With the PTWA method, a thin ferrous coating is applied to the previously roughened cylinder liner.

The coating material in the form of a wire is initially melted on by means of an electric arc and an argon/hydrogen plasma. The molten mass is then atomised and applied to the roughened cylinder liner. The collision of the atomised mass with the substrate results in solid interlocking of the materials. A lamellar coating with a defined porosity is thus produced step-by-step which guarantees a high degree of oil adhesion during engine operation.



Cylinder liner with PTWA coating  
(before honing)

1\_10\_17




Cylinder liner after honing

1\_11\_17

A low-friction, smooth and dimensionally accurate cylinder liner is produced by subsequent multi-stage mechanical honing.

## 718 Boxster/S Model Year 2017 (982)



PTWA application



1\_12\_17



Wear assessment of PTWA cylinder liners is primarily carried out by means of visual inspections (similar to ALUSIL liners). The assessment criteria are discolorations and surface damage.



## 718 Boxster/S Model Year 2017 (982)




Crankshaft drive for the flat-four engine

1\_02\_17

### Crankshaft drive

The design of the crankshaft drive is largely based on the design for the flat-six engines.

### Crankshaft



Crankshaft for the flat-four engine

1\_13\_17

The crankshaft is supported by six bearings (five main bearings and one support bearing). The bearings and bearing dimensions correspond to the six-cylinder engines (lead-free ternary bearings with steel backing, main bearing diameter 63 mm, support bearing diameter 52 mm).

The bearings 1, 3, 5 and 6 (support bearing) are smooth bearings and bearings 2 and 4 are grooved bearings. Oil is supplied via the grooved bearings to the connecting rod bearings on the crankshaft.

Main bearing 4 is designed as a thrust bearing. Axial play is determined by two thrust washers, which are inserted at the left and right of the bearing.

The stroke is a uniform 76.4 mm for both displacement variants.

The drive for the two timing drive mechanisms (each with duplex chain) and the demand-controlled oil pump (with simplex chain) is located on the pulley side.



## 718 Boxster/S Model Year 2017 (982)

### Connecting rod



Connecting rod

1\_14\_17

Forged steel rods with a cracked big end are used. The connecting rod eyes have a diameter of 22 mm in the 2.0 l version and 23 mm in the 2.5 l version.

Like for the main bearings, lead-free ternary bearings are used as the connecting rod bearings.

### Pistons



Piston on 718 Boxster MY17

1\_15\_17

Piston on 718 Boxster S MY17

1\_16\_17

Aluminium forged pistons are used in the flat-four engines. The piston diameter is approx. 91 mm for the 2.0 l variant and approx. 102 mm for the 2.5 l variant.



The connecting rods are classified according to weight and can therefore be replaced only as a set (four rods).



Please observe the specifications in the current Workshop Manual for piston assembly!

## 718 Boxster/S


### Model Year 2017 (982)

Engine

# 1



Observe the installation position of the piston rings in accordance with the Workshop Manual!



Heat shield of oil pan


1\_18\_17

### Piston rings

Three piston rings are fitted on the piston (from top to bottom):

- Steel plain compression ring
- Stepped taper-faced ring
- Three-piece oil scraper ring

### Oil pan




Two-piece oil pan

1\_17\_17

The oil pan of the flat-four engines comprises two parts. Unlike on the flat-six engines, it is made of aluminium. This was necessary due to the direct proximity of the exhaust system. A heat shield plate is installed between the oil pan and turbocharger in order to additionally reduce the effect of heat.

### 1.2.4 Cylinder head



Cylinder head

1\_19\_17

The design of the cylinder heads was derived from the six-cylinder variant. They are made from AlSi7Cu3Mg and are cast using the Rotacast process (with subsequent heat treatment).

The spark plug and high-pressure injector are located centrally in the combustion chamber directly next to each other. As a result, the intake and exhaust camshafts are positioned relatively far apart (147 mm).

The camshafts are supported directly in the cylinder head by means of a double bearing saddle and two individual bearing covers in each case.

#### Valve covers

The engine/transmission suspension was changed from three-point to four-point mounting. For this purpose, there is a bearing bracket on each of the two valve covers which supports the engine mounts on the left and right respectively. The bearing bracket is screwed together with the valve cover.



- 1 Spark-plug recess
- 2 Injector bore



The spark-plug recess is slightly angled. For this reason, an angle extension must always be used for disassembly and assembly of the spark plugs. The spark plug must be carefully inserted in the recess in order to avoid deformation of the electrodes. Attention! There is a risk of damage if this is not observed.




Different spark plugs are used in the 2.0 l and 2.5 l engine variants:


- 718 Boxster MY17: Bosch
- 718 Boxster S MY17: NGK

Attention: Danger of confusion!

## 718 Boxster/S Model Year 2017 (982)




Engine



Valve cover with engine mount

1\_21\_17


- 1 Valve cover
- 2 Bearing bracket
- 3 Engine mount



Valve cover with bearing bracket

1\_20\_17

### Camshafts



Radial and axial splines on shaft and cam

1\_24\_17

Positive connection of shaft and cam

1\_25\_17


The assembled camshafts already familiar from other engine concepts are also used in the flat-four engines. In a manufacturing process, the cam profiles with axial splines are pressed on over radial splines on the camshaft tube to produce a positive connection.



## 718 Boxster/S Model Year 2017 (982)

### Valve drive


Both the intake and exhaust camshafts have the familiar vane adjusters with central valve. Porsche VarioCam Plus valve lift adjustment is used on the intake and exhaust valves.



Valve drive

1\_22\_17

### 1.2.5 Timing drive mechanism



Timing drive mechanism


1\_23\_17

The timing drive mechanism was adopted fully from the flat-six engines. The intake and exhaust camshafts of both cylinder banks are each driven by a separate duplex roller chain with 8 mm pitch and 146 chain links. The chain tensioners operate hydraulically and are equipped with a helper spring. In comparison with the 9A1 engine generation, it was possible to approximately halve the spring preload by means of an optimised oil pressure line. This in turn further reduces friction and wear.



“9A1” is the development designation of the first DFI flat engine (911 Carrera as of MY09).

## 718 Boxster/S Model Year 2017 (982)



The crankshaft must be turned on by one revolution between adjustment of the left and right timing drive mechanisms! Please also observe the current Workshop Manual!


The oil pump is driven separately via a single simplex roller chain. The chain tension is ensured here by a mechanical chain tensioner.

### Valve timing



Staking tool 9772/1

1\_26\_17




Installation position of staking tool

1\_27\_17

The timing is adjusted in a similar way to the flat-six engine. The already familiar special tool 9772/1 (two-part) is used for positioning the camshafts. The tool is installed instead of a camshaft bearing cover in each case.

### 1.2.6 Oil supply



Oil circuit

1\_25\_17

## 718 Boxster/S Model Year 2017 (982)

### Oil mist separator


The oil-mist separator is located above the crankcase. The pressure-regulating valve is integrated in the housing.

### Oil-filter housing

Like on the previous models, the oil-filter housing is accessible from below. To permit easier handling, there is a drip funnel on the oil filter base which allows the emerging oil to be drained in a directed way when the filter is changed.



### Oil/water heat exchanger

The oil/water heat exchanger is mounted on the top of the crankcase. In addition to the two coolant connections, there is a coolant bleeding connection on the top of the housing.



Additional components for oil circuit

1\_24\_17



Oil-filter housing

1\_26\_17


- 1 Drip funnel




In order to avoid soiling of the rear axle when the oil filter is changed, a corresponding commercially available hose must be fitted on the connection piece of the drip funnel.

- 1 Oil mist separator
- 2 Oil/water heat exchanger
- 3 Coolant bleeding connection
- 4 Oil-filter housing

## 718 Boxster/S Model Year 2017 (982)







- 1 Oil pump drive
- 2 Extraction at cylinder heads
- 3 Vane pump
- 4 Extraction at turbocharger
- 5 Electrical connection for control valve
- 6 Control valve



Oil pump (rear view)

1\_28\_17


- 1 Control valve
- 2 Extraction at cylinder heads
- 3 Electrical connection for control valve



Displays for oil level measurement

1\_29\_17

### Oil pump



Oil pump

1\_27\_17

A modular oil pump is installed. However, unlike in the flat-six engines, a one-stage pressure pump is used in the flat-four engines (six-cylinder engine: two-stage pressure pump).

The pressure oil pump is a continuously variable vane pump. For this purpose, the control valve on the pump is energised via the DME control unit. If activation fails, the pump is mechanically adjusted to "high delivery output".

Three oil scavenge pumps are integrated in the pump housing. These extract the oil from the cylinder heads and at the turbocharger.

### Oil level measurement


Like in the previous models, oil level measurement is performed by means of an electronic oil level sensor. The result of the measurement is displayed on the instrument cluster.



## Piston crown cooling

Like on the flat-six engines, spray nozzles are installed in the crankcase for piston crown cooling. These have a mechanical pressure valve which opens at 2.4 bar. The valve closes at 1.8 bar when the oil pressure falls. This means that a sufficient oil pressure can be ensured at the bearing locations even at low engine speeds, particularly when the engine is hot and when the engine oil has correspondingly low viscosity.

### 1.2.7 Cooling system



High and low-temperature cooling circuits

1\_30\_17

The flat-four engines feature a high-temperature cooling circuit and a low-temperature cooling circuit.

#### Repair

Bleeding of the high-temperature and low-temperature cooling circuits takes place jointly. The filling device 9696, bleeding adapter 9696/1 and vacuum pump VAS 6096/2 are required for proper bleeding. All shut-off valves of the thermal management system must be open during the bleeding procedure. This takes place via a corresponding guided procedure defined in the PIWIS Tester.




Both cooling circuits are described in detail in Group 2.

- 1 High-temperature cooling circuit
- 2 Low-temperature cooling circuit



After disassembly of the indirect charge-air cooler, e.g. for assembly work on the engine, where coolant escapes from the system, the cooling system must be completely bled!



Filling device 9696

1\_33\_17

## 718 Boxster/S Model Year 2017 (982)

Engine

# 1



Drive unit with rear axle on lifting table

1\_34\_17


When carrying out bleeding, the coolant expansion tank is filled up to the “MAX” marking. No coolant must be topped up if a subsequent visual inspection shows that the coolant level has fallen below the “MAX” marking! Coolant must be topped up only if the messages “Refill coolant” or “Refill coolant immediately” are displayed on the instrument cluster.

### 1.2.8 Special tools

#### Engine removal and installation

Due to the four-point mounting, the engine is removed together with the transmission and rear axle.

The chassis must be correspondingly measured and if necessary adjusted after installation.




Engine support points

1\_35\_17

The engine support points have been changed compared with the six-cylinder variant. The rear support point is on the oil pan. The support point on the lifting table is provided with a rubber pad at the corresponding location.

## Removing and installing the piston pins



Piston pin assembly opening

1\_36\_17

In order to permit disassembly and assembly of the piston pins and circlips, both the flat-four engines have one service opening in the output (flywheel) and belt drive sides in the crankcase half for cylinders 3 – 4.

The familiar tools for the flat-six engine are used on the belt drive side.



New, shorter tools are used for work on the output side in order to avoid a collision with the mounting of the engine/transmission repair stand:

- Disassembly tool for piston-pin circlips, short
- Assembly tool for piston-pin circlips, short
- Disassembly/assembly tool for piston pins, short
- Centring mandrel for piston/connecting rod, short

Due to the different piston pin diameters of the two displacement variants, the corresponding tools are available in two diameters.



## 718 Boxster/S Model Year 2017 (982)



Vibration damper with decoupled belt pulley and conventional vibration damper 1\_37\_17

1 Staking bores

### Adjustment work on timing drive mechanism/staking the crankshaft


For design reasons, the vibration damper with decoupled belt pulley does not have any staking bores for positioning the crankshaft. The procedure described in the current Workshop Manual must be followed when carrying out adjustment work.

The special tool 9772/1 is used for staking the camshafts.

### Bleeding the cooling system

The following special tools are required for bleeding the cooling system properly:

- Filling device 9696,
- Bleeding adapter 9696/1,
- Vacuum pump VAS 6096/2.



Filling device 9696

1\_33\_17



Vacuum pump VAS 6096/2

1\_38\_17


It is recommended to position the canister of filling device 9696 as high as possible, e.g. using a ladder. This significantly assists the coolant flow during the bleeding procedure.





## **Group 2**


# **DME engine electronics**



## 2 DME engine electronics

### 2.1 Introduction

The flat engines from Porsche have been renowned for their outstanding features for decades: compact design, low centre of gravity, high revving stability, immediate responsiveness, a characteristic sound and surprisingly low fuel consumption. All of these are characteristics that a Sports Car designer wants from an engine. And the new 4-cylinder turbo engines offer exactly these characteristics.



2.0 I 4-cylinder turbo engine 718 Boxster MY17

2\_01\_17

They have made it possible to realise the largest increase in torque and power that has ever been achieved in the history of the Boxster with the introduction of a new engine.

## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

2

<b>2.1</b>	<b>Introduction</b>	<b>25</b>
<b>2.2</b>	<b>2.0 I/2.5 I flat-four engine with turbocharger</b>	<b>27</b>
2.2.1	Technical data	27
2.2.2	Fuel system	29
2.2.3	Intake system	33
2.2.4	Turbocharging	38
2.2.5	Mixture formation	42
2.2.6	Ignition system	46
2.2.7	Exhaust system	47
2.2.8	Thermal management	51
2.2.9	Additional DME functions	56
2.2.10	DME control unit	
	SDI 21.1	61


## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

# 2

### Development objectives

The engines of the new Boxster generation are a completely new development. During the development of the engines, particular attention was paid to transferring the typical virtues of a naturally aspirated engine, such as excellent responsiveness and a high-revving engine characteristic, to a turbo engine. This was achieved in an impressive manner. The maximum engine speed of the 718 Boxster/S MY17 is 7,500 rpm. This is an impressive value for turbocharged engines and is previously unrivalled in the segment.



2.0 l 4-cylinder turbo engine 718 Boxster MY17

2\_02\_17

The technical solution for this:

- Downsizing of the displacement by 4-cylinder technology in combination with turbocharging. On the 718 Boxster MY17, turbocharging is performed by a turbocharger with integrated wastegate. On the 718 Boxster S MY17, turbocharging takes place by means of a VTG turbocharger, also with integrated wastegate. The displacement was adapted to 2.0 l in the 718 Boxster and 2.5 l in the S model. This corresponds to a reduction of 0.7 litres for the 718 Boxster model and 0.9 litres for the 718 Boxster S model.
- The cylinder heads are also new. The intake and exhaust ports have been flow-optimised and feature efficient cross-flow cooling.
- The turbo engines of the 718 Boxster MY17 models feature efficient indirect charge-air cooling.



One of the development goals was to achieve sporty performance with lower CO<sub>2</sub> emissions. This technology made it possible to reduce CO<sub>2</sub> emissions by up to 13% in spite of a significant increase in power.

## **2.2 2.0 I/2.5 I flat-four engine with turbocharger**

### **2.2.1 Technical data**

The new turbo engines offer the same level of responsiveness as naturally aspirated engines, but deliver 100 and 60 Nm more torque and 35 hp more power than the naturally aspirated engines of the previous model. The torque curve is significantly higher over the entire rpm range, which offers noticeable advantages for driving performance.

	<b>718 Boxster MY17</b>	<b>718 Boxster S MY17</b>
<b>Combustion process</b>	DFI	DFI
<b>Swept volume</b>	1,988 cm <sup>3</sup>	2,497 cm <sup>3</sup>
<b>Bore</b>	91 mm	102 mm
<b>Compression ratio</b>	9.5:1	9.5:1
<b>Engine power at engine speed</b>	220 kW (300 hp) 6,500 rpm	257 kW (350 hp) 6,500 rpm
<b>Torque at engine speed</b>	380 Nm 1,950 – 4,500 rpm	420 Nm 1,900 – 4,500 rpm
<b>Max. engine speed</b>	7,500 rpm	7,500 rpm
<b>Idle speed</b>	800 ± 50 rpm	800 ± 50 rpm
<b>Throttle valve</b>	57 mm	74 mm

The engine of the 718 Boxster S differs from that of the 718 Boxster by virtue of the larger displacement as well as the use of a large (familiar from the 911 Turbo) VTG turbocharger with integrated wastegate and a modified engine control.




## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

2

- 1 Torque (Nm)
- 2 Engine power (kW)

### Power and torque diagrams




Power/torque diagram for 718 Boxster MY17

2\_03\_17

The 718 Boxster offers a constantly available torque of 380 Nm between 1,950 rpm and 4,500 rpm. The maximum torque increased from 280 Nm to 380 Nm (+100 Nm) in the 718 Boxster models. This provides for significantly increased elasticity values and excellent acceleration reserves.

The power output was increased by 35 hp for both models. The 718 Boxster models now produce 220 kW (300 hp) and the 718 Boxster S models 257 kW (350 hp).



Power/torque diagram for 718 Boxster S MY17

2\_04\_17

The maximum torque of the 718 Boxster S models increased from 360 Nm to 420 Nm (+60 Nm) and is available as a constant torque between 1,900 rpm and 4,500 rpm.

## 2.2.2 Fuel system

### Fuel quality


The engine is designed to provide optimum performance and fuel consumption if unleaded fuel without metal additives with 98 RON/88 MON is used.

### Low-pressure system

The fuel tank and activation of the electric fuel pump are essentially comparable with the previous 981 models.

The tank capacity is approx. 64 l for the Boxster S and approx. 54 l (optionally 64 l) for the Boxster, including 8 l reserve capacity. The control unit supplies the electric DC fuel pump with power, and the pressure regulator in the fuel tank limits the low pressure to max. 6 bar.

Like on the 981, the control unit for activation of the electric DC fuel pump is located under the battery holder.




Fuel tank

2\_43\_17

### Fuel low-pressure sensor

For measuring the fuel low pressure, the engines are equipped with a fuel low-pressure sensor, which is located on the left cylinder bank (bank 2) in the low-pressure line upstream of the fuel high-pressure pump. This enables regulation of the fuel low pressure between 3.5 and 6.0 bar depending on the fuel requirement.



Fuel


2\_05\_17

- 1 Fuel low-pressure sensor
- 2 Low-pressure line
- 3 Fuel high-pressure pump (bank 2)

## 718 Boxster/S Model Year 2017 (982)


DME engine electronics

2



Fuel high-pressure pump (DFI)

2\_07\_17



Fuel high-pressure sensor

2\_08\_17


- 1 Fuel high-pressure pump with quantity control valve (bank 2, left)
- 2 Fuel high-pressure sensor (bank 1, right)
- 3 7-hole injectors
- 4 High-pressure line (HP)
- 5 Low-pressure line (LP) from the electric fuel pump

### High-pressure system

The direct fuel injection (DFI) system has been completely redesigned. New features include the central injector position of the 7-hole injectors in the cylinder head and an increased fuel pressure. Both measures optimise the mixture formation and the combustion characteristics so effectively that, despite the use of turbocharging, it was possible to dispense with secondary-air injection during the warm-up phase. The previous models had a side injector position with 4- or 6-hole injectors and a maximum injection pressure of 120 bar.

#### Fuel high-pressure pump with quantity control valve

The fuel high-pressure pump with quantity control valve is located on the cylinder head of bank 2 (left). This valve was enhanced to reduce noise development. The single-piston high-pressure pump is actuated by a triple cam on the intake camshaft via a roller tappet. The fuel high-pressure rails are located in the centre of the cylinder heads. Depending on the operating conditions, the quantity control valve regulates the fuel high-pressure between 125 bar and 210 bar (briefly up to max. 250 bar in the warm-up phase). The quantity control valve is activated directly by the DME control unit.



High-pressure system DFI


2\_06\_17



## 718 Boxster/S Model Year 2017 (982)


### Injectors

The central position of the 7-hole injector in the cylinder head promotes a homogeneous, symmetrical fuel distribution in the cylinder. The Boxster and Boxster S have different 7-hole injectors. The spray hole diameter and the spray pattern are matched to the respective displacement and cylinder diameter.



7-hole injector

2\_09\_17



Injector position

2\_10\_17

Voltage boosters with flexible drivers are installed in the DME control unit for injector activation.


### Special tools

The following new special tools are available for extracting the injectors and fitting new Teflon sealing rings:



Extraction tool

2\_74\_17



Assembly sleeve


2\_75\_17

- 1 Extraction tool for central injector T10133/33
- 2 Assembly sleeve for Teflon sealing ring on injector T10133/31

DME engine electronics

2

- 1 7-hole injector
- 2 Central injector position
- 3 Spark plug
- 4 O-ring (with lubrication coating)
- 5 Holding-down device (pre-assembled)
- 6 Bore seal (with lubrication coating)
- 7 Spacer ring (pre-assembled)
- 8 Circlip (pre-assembled)
- 9 Teflon sealing ring (to combustion chamber)



7-hole injector

2\_11\_17



The Teflon sealing ring must be replaced each time the injector is removed.

## 718 Boxster/S Model Year 2017 (982)


DME engine electronics

2

- 1 Ignition coil
- 2 Fuel high-pressure pump
- 3 Injector
- 4 Spark plug
- 5 High-pressure rail


### Installation positions

The illustrations show the installation positions of the spark plugs and injectors located centrally in the combustion chamber as well as the fuel high-pressure pump with quantity control valve on the cylinder head of bank 2.




Position of components in the cylinder head

2\_12\_17



Cylinder head

2\_13\_17



Bank 2 (left)

2\_14\_17



### 2.2.3 Intake system


#### Air routing

The raw air intake to the air cleaner housing takes place via the left air intake.




Left air intake

2\_15\_17



Engine compartment cover open, vehicle rear end at bottom 2\_16\_17

The intake duct is routed from the air cleaner housing to the intake side of the turbocharger installed upstream of the left cylinder bank (bank 2).



Intake system air routing


2\_72\_17

## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

2

- 1 Left air intake
- 2 Raw air intake
- 3 Air cleaner housing cover
- 4 Intake side of turbocharger
- 5 Indirect charge-air cooler (ICAC)
- 6 Hose to diverter valve
- 7 Diverter valve
- 8 Air intake on left (intake air and low-temperature module)
- 9 Air intake on right (low-temperature module)
- 10 Air cleaner housing
- 11 Turbocharger
- 12 Indirect charge-air cooler (ICAC)



Intake system air routing


2\_17\_17

## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

2

- 1 Electro-pneumatic switching valve for overrun air
- 2 Oil-filter housing
- 3 Diverter valve
- 4 Air cleaner housing cover



Connection point


2\_20\_17

- 1 Intake distributor
- 2 Intake port
- 3 O-ring
- 4 Intake manifold pressure/intake air temperature sensor (SENT)

### Diverter valve

The diverter valve is located just after the air cleaner housing in the intake duct to the turbocharger. When the diverter valve is activated by the DME control unit, a bypass is produced between the charge-air side (downstream of the indirect charge-air cooler) and the intake side of the turbocharger.

The electro-pneumatic switching valve for overrun air is located above the oil filter.



Left engine side, view from vehicle rear

2\_18\_17




Top view, vehicle rear at bottom

2\_19\_17

### Intake manifold

The intake manifold of the 718 Boxster/S MY17 consists of individual intake ports with a gas cycle-optimised length of approx. 340 mm.



Intake manifold

2\_21\_17

The connection points between intake distributor and distributor tube are sealed with O-rings.


### Intake manifold pressure/intake air temperature sensor (SENT)

The intake manifold pressure/intake air temperature sensor is located in the intake distributor.

These digital sensors transmit a SENT protocol. SENT = Single Edge Nibble Transmission.


### Boost pressure sensor (SENT)

The boost pressure sensor is installed on the indirect charge-air cooler (ICAC).



Intake manifold pressure sensor

2\_22\_17



Boost pressure sensor


2\_23\_17

### Throttle valve adjusting unit (electronic throttle)

The throttle valve adjusting unit (electronic throttle) has digital contactless rotation-angle sensors for position feedback of the throttle valve. This ensures freedom from wear and a high degree of measurement accuracy over the entire service life. In the throttle valve adjusting unit, the throttle valve, throttle valve drive and throttle valve angle sensor (Hall IMC) are integrated in one housing.

### Throttle valve sensor

The throttle valve sensor has a redundant design. The feedback of throttle valve position is via two independent, counter-rotating and contactless sensors. The generated voltage signals are comparable with those of the previously installed potentiometers.



IMC sensor and drive

2\_26\_17

- 1 IMC sensor
- 2 Drive



Adaptation of the electronic throttle must be performed with the PIWIS Tester after a reset. The lower limit position (throttle valve closed) is taught here.

## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

2

### Actuator


The actuator consists of a DC motor with two-stage gear unit. The throttle valve is positioned between the lower and upper mechanical end stops by means of an electric motor.

### Actuation

The DME control unit actuates the throttle valve electrically. Input variables for activation include the position of the accelerator pedal and requests from systems that can influence the engine torque.

### Charge-air cooling

The turbocharged Boxster engines feature newly-developed, compact and efficient low-temperature charge-air cooling. The charge air heated by the turbocharging process is cooled by an indirect charge-air cooler (ICAC) positioned above the engine.



Charge-air cooling 718 Boxster/S MY17

2\_28\_17

- 1 Indirect charge-air cooler (ICAC)
- 2 Low-temperature module, left
- 3 Low-temperature module, right
- 4 Electric low-temperature coolant pump
- 5 Low-temperature hoses
- 6 Coolant expansion tank




## 718 Boxster/S Model Year 2017 (982)



The indirect charge-air cooler is in turn cooled via an additional low-temperature (LT) cooling circuit. The heated charge air flows through the indirect charge-air cooler and gives off its heat to the coolant of the low-temperature circuit. The heat absorbed in the coolant is then dissipated to the ambient air again via the low-temperature modules accommodated in the side parts on the left and right. The low-temperature modules each comprise an air/water heat exchanger (radiator), an electric fan on the inner side as well as internally mounted ram-air flaps to optimise the air flow.

The arrangement of the low-temperature circuit and low-temperature modules with electric fan and ram-air flaps located behind the side air intakes can be easily seen from below. The heated charge air is cooled in the low-temperature modules by means of an air/water heat exchanger. The indirect charge-air cooler (ICAC) has a partially integrated low-temperature cooling circuit (LT). In other words, the high-temperature circuit (high-temperature engine cooling circuit) shares the same coolant expansion tank with the low-temperature circuit (ICAC), but otherwise operates independently of the HT circuit.




Charge-air cooling on 718 Boxster/S MY17, view from below

2\_29\_17

### Electric low-temperature coolant circulation pump

The electric low-temperature coolant pump is controlled based on demand depending on the required charge-air temperature and engine load.



Temperature ranges ICAC

2\_29\_17

- 1 Coolant temperature upstream of ICAC up to 66 °C
  - 2 Coolant temperature downstream of ICAC up to 90 °C
  - 3 Charge-air temperature upstream of ICAC up to 180 °C
  - 4 Charge-air temperature downstream of ICAC up to 72 °C
  - 5 Indirect charge-air cooler
- 
- 1 Indirect charge-air cooler (ICAC)
  - 2 Low-temperature module, left, with electric fan and ram-air flaps
  - 3 Low-temperature module, right, with electric fan and ram-air flaps
  - 4 Electric low-temperature coolant pump
  - 5 Low-temperature hoses
  - 6 Coolant reservoir

## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

2



2\_31\_17

1 Engine compartment temperature sensor

1 VTG turbocharger Boxster S

### Electric fans for the low-temperature modules right/left

The electric fans are controlled based on demand depending on the required charge-air temperature, engine load and engine compartment temperature.

They also serve as engine compartment purge fans depending on the engine compartment temperature.


### Ram-air flaps

The ram-air flaps at the exhaust-air guides of the low-temperature modules prevent recirculation of the hot air from the engine compartment through the low-temperature radiators, thus improving cooling power.

### 2.2.4 Turbocharging

The 718 Boxster/S MY17 models feature turbocharging with one turbocharger with a wastegate.

In spite of the reduction in displacement, the new engines therefore offer not just significantly higher maximum power but also a significantly higher torque over a wide engine speed range.



Installation position of VTG turbocharger in the 718 Boxster S at front left in direction of travel

2\_40\_17




## Responsiveness

When designing the turbocharging setup, particular importance was placed on the responsiveness of the turbocharger. The turbocharger is therefore “primed” during sporty driving in the part-load range. For this purpose, the wastegate valve is closed, the ignition point is retarded and the throttle valve is closed slightly.

The current drive torque thus remains the same, but the boost pressure upstream of the throttle valve is increased. During subsequent acceleration with fully depressed accelerator pedal (throttle valve wide open), a higher boost pressure and a higher torque are then immediately available.

In the event of a load change during full-load acceleration, the throttle valve is not completely closed when the accelerator pedal is released (vehicle in overrun mode). As a result, the boost pressure is not completely depleted and is available again for further acceleration following renewed actuation of the accelerator pedal. For the performance of both models, this means significantly increased elasticity, with responsiveness typical of naturally aspirated engines and a high revving ability. The torque increase is particularly evident during an intermediate sprint from 100 to 200 km/h (62 to 124 mph).

## Turbocharger Boxster



Turbocharger with wastegate in 718 Boxster MY17

2\_33\_17


## 718 Boxster/S Model Year 2017 (982)



View above bank 2 (left)

2\_32\_17

- 1 Boost-pressure control valve



Turbocharger 718 Boxster

2\_34\_17

- 1 Fresh air (intake)
- 2 Boost pressure (outlet) – to indirect charge-air cooler
- 3 Exhaust gas inlet
- 4 Turbine wheel (exhaust gas)
- 5 Exhaust gas outlet – to catalytic converter
- 6 Wastegate actuator
- 7 Wastegate

## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

2



VTG turbocharger in 718 Boxster S MY17 2\_36\_17

- 1 Fresh air (intake)
- 2 Compressor wheel (air side)
- 3 Boost pressure (outlet – to indirect charge-air cooler)
- 4 Exhaust gas inlet
- 5 Turbine wheel (exhaust gas)
- 6 VTG guide blades
- 7 Exhaust gas outlet (to catalytic converter)
- 8 Wastegate actuator
- 9 Wastegate

A turbocharger with wastegate is used for boost pressure control on the 2.0 l Boxster. The wastegate is closed by a vacuum in order to increase the boost pressure.


The maximum boost pressure of the 718 Boxster MY17 is approx. 1.4 bar. It is thus 0.3 bar higher than in the Boxster S.

### Turbocharger Boxster S

A turbocharger with the Variable Turbine Geometry (VTG) familiar from the 911 Turbo with additional wastegate is used in the 2.5 l Boxster S MY17.

The principle of variable guide blades, which guide the exhaust flow onto the turbine wheels of the turbocharger in a variable and targeted manner, combines the function of a small and large turbocharger. Here, the guide blades are practically closed for good response with high torque values at low engine speeds and are open for high output values at high engine speeds. In addition, maximum torque is available over a wide engine speed range. The maximum boost pressure of the 718 Boxster S MY17 is approx. 1.1 bar.

The additional use of a wastegate means that the exhaust backpressure can be reduced and the turbine efficiency increased by opening the wastegate in conditions with high mass throughput.



VTG turbocharger with wastegate in 718 Boxster S MY17

2\_35\_17


## 718 Boxster/S Model Year 2017 (982)

The wastegate is opened by a vacuum as required.

Use of this turbocharging technology is exceptional for turbocharged spark-ignition engines. Featuring variable turbine blades, it enables the 718 Boxster S MY17 to operate with a maximum exhaust temperature of up to approx. 980 °C. An exhaust-gas temperature sensor (SENT) is installed on turbocharger for monitoring the exhaust-gas temperature.


### Electric coolant run-on pump for turbocharger

The electric coolant run-on pump for the turbocharger is located at the front right in direction of travel on cylinder bank 1 in the 718 Boxster/S MY17. It is switched on by the DME control unit depending on the operating conditions. It can also be activated as required after the hot engine is switched off in order to cool the turbocharger by circulating the coolant.



View from front

2\_40\_17



Electric coolant run-on pump


2\_37\_17



## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

2



Position of spark plug and injector  
in the cylinder head

2\_73\_17

### 2.2.5 Mixture formation

#### Combustion chamber design

The central injector position in the cylinder head of the 4-cylinder turbo engines permits new piston crown forms compared with the previous DFI engines. On the 2.0 l engine in the 718 Boxster MY17, the piston crown has a slight recess. In contrast, the piston crown on the 2.5 l engine in the 718 Boxster S MY17 has a minimum elevation.



Piston crowns 2.0 l left/2.5 l right

2\_38\_17


Overall, the central injector is at a more uniform and greater distance to the piston crown, which improves mixture formation.

- 1 7-hole injector
- 2 Central injector position
- 3 Spark plug
- 4 Combustion chamber design in area of intake valves



Injector position and combustion  
chamber design

2\_10\_17



7-hole injector

2\_09\_17

### **Tumble intake port**

The intake ports and combustion chambers in the cylinder head have been further developed in order to increase the charge motion of the air above the piston crown. The type of charge motion used here generates an air swirl during the intake process, which rotates in the cylinder parallel to the crankshaft axis. This type of charge motion is called tumble.

### **DFI injection strategies**

Depending on the operating condition, the following injection strategies are selected:

#### **Start**

Depending on ambient temperature:

- 3x during the intake stroke
- In case of extreme cold, 3x during the compression stroke

#### **Catalytic converter heating**

- 2x during the intake stroke, 1x during the compression stroke
- Variable, other modes also possible (e.g. only 1x during intake stroke)

#### **Warm-up phase**

##### Idling

- 1x during the intake stroke

##### Acceleration with low to medium load

- 2x during the intake stroke


#### **Operating temperature**

- Single injection for small and medium load

#### **Acceleration at high load**

- 2x during the intake stroke up to 3,500 rpm
- 1x during the intake stroke above 3,500 rpm

The central injector position and the increase in the fuel pressure (to up to 250 bar) optimise mixture formation and the combustion behaviour to such an extent that it was possible to dispense with the secondary-air injection process previously used to heat up the catalytic converters. This makes it possible to achieve lower untreated exhaust gas emissions and to comply with all required exhaust emission values.



Tumble intake port

2\_41\_17



## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

2

- 1 Fuel tank
- 2 Aeration, filler neck
- 3 Carbon canister
- 4 Tank leakage diagnostic module DMTL (USA and South Korea only)
- 5 Tank ventilation to carbon canister
- 6 Carbon canister line to the engine compartment
- 7 Silencer
- 8 Tank vent valve
- 9 Check valve
- 10 Ventilation to intake port
- 11 Ventilation to intake side of turbocharger (with boost pressure)


### Tank ventilation

The carbon canister is located in the technical space above the fuel tank. The fuel tank is aerated and vented via the carbon canister. When the vehicle is being driven, venting takes place into the intake system by clocked operation of the tank vent valve (via the check valve directly into the intake port when a vacuum is present and into the intake side of the turbocharger when boost pressure is present).




Fuel low-pressure line

2\_42\_17



Fuel tank with carbon canister

2\_43\_17



Tank ventilation


2\_44\_17

### **Tank leakage diagnostic module (DMTL)**

On vehicles for the USA and South Korea, a tank leakage diagnostic module (DMTL) is installed for tank ventilation diagnosis. The function of the DMTL has already been described for the 987.

### **Crankcase ventilation**

Crankcase ventilation takes place via the positive crankcase ventilation valve with oil separator. When there is a vacuum in the intake port, ventilation takes place directly into the intake port via the vent line and check valve. When charge pressure is present, ventilation takes place into the intake side of the turbocharger.



Crankcase ventilation

2\_44\_17

- 1 Crankcase ventilation/oil separator
- 2 Ventilation to the intake port (at idle speed)
- 3 Ventilation to intake side of turbocharger (with boost pressure)
- 4 Ventilation of the cylinder heads

- 1 Ignition coil with integral ignition driver
- 2 Captive steel screw
- 3 Spark plug connector with contacting spring
- 4 Contact plate for contacting with spark plug connector
- 5 Spark plug with one ground electrode



Different spark plugs are installed in the 718 Boxster/S MY17!

A special bi-hexagonal socket with a width across flats of 14 mm is required to remove the spark plugs. The spark-plug recess is slightly angled. For this reason, a flexible extension (a/f 14) must be used in all cases.

## 2.2.6 Ignition system

### Individual ignition coils

The individual ignition coils are fitted with a captive steel screw. The newly developed ignition coils in the "plug top" design with integral ignition driver are designed for a higher ignition voltage requirement (over 30 kV).



Individual ignition coil

2\_45\_17

### Spark plugs

Different air-gap spark plugs with one ground electrode are used on the 718 Boxster and 718 Boxster S.

The spark plugs have a modified high-voltage terminal with contact plate for contacting. The new contacting design requires optimum seating of the ignition coil contacting spring on the contact plate of the spark plug. Slight coating of the silicone sheath with talcum powder is necessary to facilitate re-installation and above all removal of the ignition coil.



## Knock control


The DME control unit features enhanced signal evaluation for knock detection. The engine is designed for a fuel octane rating of 98 RON. If 95 RON is used, the knock control responds accordingly, which can result in reduced engine power.

## Knock sensors

The flat-four engine has two knock sensors on the engine block for knock detection.

### 2.2.7 Exhaust system

The sound of a flat engine is something very special and contributes significantly to the particularly emotional driving experience in a 718 Boxster. The sound is especially emotional in the higher engine speed range. The use of turbo technology in the 718 Boxster MY17 models naturally affects the character of the engine sound. To ensure that the 718 Boxster MY17 continues to offer an emotional sound experience that is typical for Porsche, three completely new exhaust systems were developed. The Boxster and Boxster S have twin-branch manifolds, a single-branch catalytic converter and a twin-branch silencer.



Exhaust system 718 Boxster/S MY17 (tailpipes of Boxster S)

2\_47\_17



The country-specific change intervals for the spark plugs, plug type, heat rating and tightening torques can be found in the PIWIS information system/maintenance schedule.


- 1 Air gap-insulated exhaust manifolds on left/right with connecting pipe
- 2 Catalytic converter
- 3 Oxygen sensor downstream of catalytic converter
- 4 Intermediate pipe (with integral insulation)
- 5 Main silencers, left/right (sports exhaust system with flap on right)
- 6 Tailpipes (718 Boxster S)
- 7 Transmission suspension
- 8 Tension bands for transmission suspension
- 9 Main mounting – load-carrying, on engine
- 10 Bracket with shock element
- 11 Bracket with vibration compensation

## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

# 2

- 9 Main mounting – load-carrying, on engine
- 10 Bracket with shock element
- 11 Bracket with vibration compensation



3 bracket versions in exhaust system area

2\_48\_17

### Exhaust gas routing

The exhaust gases of the two cylinder banks 1 and 2 are merged upstream of the turbocharger. The single-branch catalytic converter is flanged directly onto the turbocharger outlet. After the catalytic converter, the exhaust gas flow is branched towards the left and right rear silencers.



- 1 Merging upstream of the turbocharger
- 2 Turbocharger
- 3 Catalytic converter
- 4 Branching to left and right silencers

View from below, front of vehicle


2\_49\_17



## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

2




View from below, rear of vehicle

2\_50\_17

The two silencers are connected with each other twice via connecting pipes. The two tailpipes, which are additionally provided with covers, are welded on at the rear connecting pipe.


### Emission control



Installation positions of oxygen sensors

2\_49\_17

- 1 LSU oxygen sensor upstream of catalytic converter, bank 1 (right)
- 2 LSU oxygen sensor upstream of catalytic converter, bank 2 (left)
- 3 LSF oxygen sensor (in the catalytic converter)
- 4 Catalytic converter



Catalytic converters 718 Boxster/S MY17

2\_51\_17

- 1 Catalytic converter 718 Boxster
- 2 Catalytic converter 718 Boxster S

## 718 Boxster/S

### Model Year 2017 (982)


DME engine electronics

2

The engines and the emission control are designed for low untreated exhaust gas emissions and comply with all stringent emissions legislation worldwide, such as EURO 6 ZD stage 2 and USA LEV III, ULEV 125.

#### Silencers

The silencers for the 718 Boxster and 718 Boxster S are identical apart from the tailpipes.



Internal design of silencers on 718 Boxster/S (tailpipe 718 Boxster S)

2\_52\_17

#### Tailpipe 718 Boxster

The 718 Boxster features a twin-branch exhaust system with an oval single-tube tailpipe made of brushed stainless steel.



Tailpipe 718 Boxster MY17

2\_53\_17



Tailpipe 718 Boxster S MY17

2\_54\_17

#### Tailpipe 718 Boxster S

The 718 Boxster S is equipped with a twin-branch exhaust system with centrally arranged round twin tailpipes made of brushed stainless steel.

#### Sports exhaust system (optional)


The sports exhaust system optionally available for all models has two centrally arranged round sports tailpipes. The tailpipes of the sports exhaust system are available in silver or black.



Black tailpipe for sports exhaust system

2\_55\_17

## 718 Boxster/S Model Year 2017 (982)



Sports exhaust system (option) with flap on right

2\_56\_17

This exhaust system features a flap control which opens the exhaust flap on the right silencer depending on the engine speed as from approx. 3,500 rpm. This reduces the exhaust backpressure for even better power development and an even more emotional, rich flat-engine sound.

The exhaust flap can be activated by means of a button in the centre console.

### 2.2.8 Thermal management

Like the previous model, the 718 Boxster MY17 is also equipped with thermal management for the reduction of fuel consumption and CO<sub>2</sub> emissions, particularly after cold starting.

The following conditions are met through thermal management, for example:

- Operating temperature is reached quickly after cold starting
- Fast adjustment to calculated setpoint temperature (105 °C – 85 °C) depending on operating conditions
- High coolant throughput at full throttle. Here, the engine, transmission and heating are warmed up more quickly through demand-based activation of various partial cooling circuits.

The tasks and function of thermal management were already described in detail for the Boxster 981.




DME engine electronics



Centre console button

2\_57\_17

## System overview



Function overview of thermal management

2\_59\_17



When filling and bleeding the HT and LT cooling circuits and checking the coolant level, the specifications of the PIWIS information system must be observed in all cases.

- |   |   |
|---|---|
| 1 1-4 cylinders                                     | 15 Gear wheel set heat exchanger            |
| 5 Left radiator                                     | 16 Shut-off valve for clutch heat exchanger |
| 6 Right radiator                                    | 17 Clutch heat exchanger                    |
| 7 Centre radiator (super hot countries only)        | 18 Electric run-on pump for turbocharger    |
| 8 Switched coolant pump                             | 19 Turbocharger                             |
| 9 Thermostat with electrical map control            | 20 Coolant expansion tank                   |
| 10 Coolant shut-off valve                           | 21 Comfort valve with bleeding lever        |
| 11 Engine oil/water heat exchanger                  | 22 Filler tube check valve, LT              |
| 12 Shut-off valve for heating heat exchanger        | 23 Electric pump, low-temperature           |
| 13 Heating heat exchanger                           | 24 Low-temperature radiator, left           |
| 14 Shut-off valve for gear wheel set heat exchanger | 25 Low-temperature radiator, right          |
|   | 26 Indirect charge-air cooler (ICAC)        |
|   | 27 Check valve for LT ventilation           |



## 718 Boxster/S Model Year 2017 (982)


### Changes compared with 981 Boxster MY12-16

- Additional low-temperature circuit with the indirect charge-air cooler (ICAC) and an electric coolant pump for charge-air cooling
- After a cold start, the switched coolant pump is closed by means of vacuum in order to achieve faster warming-up through the standing coolant
- The electric coolant after-run pump for the turbocharger guarantees cooling of the turbocharger even after the engine is switched off

The side graphic shows the faster increase in coolant temperature after a cold start in comparison with the previous models.


### High-temperature circuit (HT) and low-temperature circuit (NT)

A new feature is the low-temperature circuit with the indirect charge-air cooler (ICAC) for charge-air cooling.



Temperature increase after cold start

2\_58\_17



Components of the cooling system

- |  |                                      |
|--|--------------------------------------|
| 1 Left radiator                              | 7 Coolant line from the radiators    |
| 2 Right radiator                             | 8 Low-temperature module, right      |
| 3 Centre radiator (super hot countries only) | 9 Low-temperature module, left       |
| 4 Radiator fan, left                         | 10 Indirect charge-air cooler (ICAC) |
| 5 Radiator fan, right                        | 11 Coolant expansion tank (HT/LT)    |
| 6 Coolant line to the radiators              | 12 Heater valve                      |

- Exhaust system
- HT cooling system
- LT cooling system
- Intake air routing

2\_60\_17




Vacuum filling of the low-temperature circuit is necessary after removing and installing the indirect charge-air cooler.



- 1 Coolant supply
- 2 Map-controlled thermostat
- 3 Coolant pump (switched)
- 4 Coolant shut-off valve
- 5 Electric coolant run-on pump for turbocharger
- 6 Transmission heat exchanger
- 7 Oil-water heat exchanger
- 8 Coolant return line

### Cooling system, components on engine



Cooling system components on engine

2\_61\_17

### Switched coolant pump

Depending on the cooling requirement, the switched coolant pump is switched according to demand in two stages and makes a further contribution to reducing fuel consumption and CO<sub>2</sub> emissions.

The coolant flow is stopped (standing coolant) in fully closed state. The switched coolant pump is open and coolant is circulated when the engine is at operating temperature.

- 1 Closed after cold start and in the warm-up phase (vacuum present)
- 2 Connection for vacuum line
- 3 Coolant pump open (coolant is circulated, no vacuum present/aerated)



Coolant pump closed

2\_62\_17



Coolant pump open

2\_63\_17




View of bank 1, front

2\_39\_17

### Coolant expansion tank

The high-temperature and low-temperature circuits use the same coolant expansion tank.



Coolant expansion tank

2\_64\_17

- 1 Electro-pneumatic switching valve for switched water pump
- 2 Electro-pneumatic switching valve for coolant shut-off valve


- 1 Expansion tank for high- and low-temperature circuits
- 2 Filler neck with level indicator
- 3 Comfort valve
- 4 Venting – engine and radiator

## 718 Boxster/S Model Year 2017 (982)

DME engine electronics

2

- 1 Coolant shut-off valve in heating tube
- 2 Vent lines
- 3 Coolant supply and return lines



Coolant lines


2\_65\_17

### 2.2.9 Additional DME functions

#### VarioCam Plus

The VarioCam Plus variable valve control on the intake camshafts has been significantly extended. The system now additionally features continuous VarioCam Plus camshaft control with valve-lift adjustment of the exhaust camshafts.

- 1 Central valve, intake camshaft
- 2 Vane adjuster
- 3 Hall-sender rotor
- 4 Valve lift switching valve (intake)
- 5 Switchable bucket tappets
- 6 Roller tappet for high-pressure pump
- 7 Central valve, exhaust camshaft
- 8 Vane adjuster
- 9 Hall-sender rotor
- 10 Valve lift switching valve (exhaust)



VarioCam Plus

2\_66\_17



## 718 Boxster/S Model Year 2017 (982)

This permits high power and torque values as well as favourable fuel consumption and low exhaust emissions. This also improves the responsiveness of the turbochargers. Depending on the engine operating conditions, the following adjustments are possible:

### Intake camshaft

- Continuous: 0° crank angle to max. 50° crank angle
- Valve lift (small): 3.60 mm
- Valve lift (large): 718 Boxster: 9.90 mm/718 Boxster S: 10.00 mm

### Exhaust camshaft


- Continuous: 0° crank angle to max. 55° crank angle
- Valve lift (small): 5.30 mm
- Valve lift (large): Cylinders 1+3: 8.71 mm/Cylinders 2+4: 9.90 mm

### Dynamic control of oil pressure

The oil supply is realised by means of a variable oil pump. The valve for dynamic oil pressure control is activated by the DME control unit.

### Sport Chrono package

The Sport Chrono package is the first choice for increasing the driving performance and driving pleasure. This package has been significantly redesigned for the 718 Boxster MY17. The various driving modes are now no longer selected using buttons on the centre console, but instead via the Mode switch located in the redesigned steering wheel. Individual mode is now available in addition to the three existing modes Normal, SPORT and SPORT PLUS. The settings for the PASM, sports exhaust system, Auto Start Stop function and rear spoiler can be combined individually based on Normal mode or SPORT modes via a corresponding menu in the instrument cluster. The saved combination can be retrieved the next time the vehicle is started by turning the Mode switch to position I.



Oil pump and oil pressure control

2\_67\_17

- 1 Electro-hydraulic valve for dynamic oil pressure control



Mode switch

2\_68\_17

## 718 Boxster/S

### Model Year 2017 (982)

DME engine electronics

2



Sport Response function

2\_69\_17

With the Sport Chrono package, the standard SPORT button in the centre console is omitted. The stopwatch in the dashboard upper section remains part of the package.

#### **Sport Response Button (vehicles with PDK only)**

Another new function in the Sport Chrono package is the SPORT Response button located in the centre of the Mode switch on vehicles with PDK. Inspired by motor sport, the SPORT Response button on the 718 Boxster MY17 gives the driver the option of changing the responsiveness of the vehicle directly at the press of a button.

When the SPORT Response button is pressed, the engine and transmission are prepared for maximum responsiveness. In the part-load range, the wastegate for the turbocharger is closed to allow the boost pressure to build up more quickly. The engine responds much more directly to accelerator pedal commands and reaches maximum power more quickly. At the same time, the PDK switches to a special shift map.

In part-load range, the PDK immediately switches back to an engine speed range of between 4,500 to 6,000 rpm. At this point, the shift map is moved upwards again so that the PDK only switches to the next-higher gear at a later time, thereby retaining the extremely direct responsiveness of the high engine speed range for a few hundred revolutions longer.

A countdown timer on the display in the instrument cluster informs the driver how much longer the SPORT Response function will remain active before the vehicle reverts back to the previously selected mode after 20 seconds have elapsed. The SPORT Response function can be activated as often as required. Pressing the SPORT Response button again while the function is active, deactivates the function.

#### **Coasting mode (vehicles with PDK)**

Coasting mode is designed primarily for reducing fuel consumption and emissions. Coasting is driving at idle speed without any engine braking effect. Coasting takes place after the accelerator pedal has been fully released in the normal way. A distinction is made between the functions of coasting and intelligent trailing throttle fuel cutoff depending on the operating condition.



In SPORT mode, the focus is on the fun factor and the sound. In SPORT PLUS mode, maximum performance is made available.

### **Intelligent trailing throttle fuel cutoff (ISA)**

With intelligent trailing throttle fuel cutoff (ISA), the application is optimised for the interaction between engine and PDK transmission in order to achieve further fuel consumption benefits.

The engine resumption speed was reduced to 860 rpm (previously 1,088 rpm). This was made possible by detection of the brake pressure. When driving in virtual gears (with the clutch not fully closed), closing the throttle triggers downshifts to enable prolonged overrun operation of the engine.

### **Virtual gears**

The virtual transmission ranges already familiar from the 911 Turbo were implemented in conjunction with the PDK to increase efficiency (fuel saving potential). If the transmission control detects that the vehicle is travelling at a constant speed, it shifts to a higher gear until the engine would in theory turn at approx. 800 rpm.

To maintain driving comfort, the transmission control increases the engine speed automatically by the clutch allowing slight slip, but only within a range (with low engine load) that does not increase wear. The driver remains totally unaware of these sophisticated technical processes.

### **Extended Auto Start Stop function**

Specific optimisations of various systems such as the PDK also contribute to a reduction in fuel consumption on the 718 Boxster MY17 models. For example, the 718 Boxster models now feature the enhanced Auto Start Stop function, which already switches the engine off when the vehicle is rolling to a stop situation (at a speed of less than 2 km/h (1.2 mph)). The detailed conditions/prerequisites are described in the Owner's Manual.



Auto Start Stop button on centre console

2\_70\_17

### **Electric sound actuator**

In addition to the new exhaust systems, an electric sound actuator is responsible for creating an emotional Porsche-specific sound in the passenger compartment of the vehicle. The electric sound actuator is installed on the front engine cover in the passenger compartment. It is activated by means of a separate control unit connected with the CAN bus. This control unit is located at the rear left of the luggage compartment.



Electric sound actuator

2\_24\_17

The goal of the sound actuator is to support/enrich the engine-specific sound, whereby the acoustic component of the sound actuator should harmonise with the sound of the engine and exhaust system depending on load, engine speed and driving speed.


## **2.2.10 DME control unit SDI 21.1**

### **Overview of sensors**

- Accelerator pedal sensor (electronic)
- Throttle valve sensor (electronic)
- Fuel high-pressure sensor
- Fuel low-pressure sensor
- Pressure sensor for tank ventilation (vehicles with DMTL only)
- Engine oil temperature sensor
- Coolant temperature sensor 1 (cylinder head)
- Engine compartment temperature sensor
- Coolant temperature sensor 2 (radiator outlet)
- Transmission oil temperature sensor (gear wheel set)
- Brake vacuum sensor
- Oxygen sensor downstream of catalytic converter
- Oxygen sensor upstream of catalytic converter, bank 1
- Oxygen sensor upstream of catalytic converter, bank 2
- Knock sensor, bank 1
- Knock sensor, bank 2
- Engine speed sensor (Hall) (crankshaft)
- Intake camshaft sensor, bank 1
- Intake camshaft sensor, bank 2
- Exhaust camshaft sensor, bank 1
- Exhaust camshaft sensor, bank 2
- Transmission speed sensor (MT)
- Neutral gear sensor (MT)
- Duo-sensor (oil temperature and oil level sensor, PULS II)
- Brake pedal sensor
- Clutch sensor (MT)
- PDK P/N
- Crash signal
- Intake manifold pressure/intake manifold temperature sensor (SENT)
- Boost pressure sensor (SENT)
- Exhaust temperature sensor (SENT) – only for VTG turbocharger
- Oil pressure sensor (SENT)

### **CAN connections**

- CAN Drive



DME control unit SDI 21.1

2\_71\_17

## Overview of actuators

- Throttle valve servo motor
- DME relay
- High-pressure injector, cylinder 1 to cylinder 4
- Ignition module, cylinder 1 to cylinder 4
- VarioCam Plus, intake, cylinders 1+2
- VarioCam Plus, exhaust, cylinders 1+2
- VarioCam Plus, intake, cylinders 3+4
- VarioCam Plus, exhaust, cylinders 3+4
- Diverter valve (electro-pneumatic)
- Coolant shutoff valve (coolant bypass)
- Coolant shut-off valve (gear wheel set cooling PDK + MT)
- Coolant shut-off valve (PDK clutch cooling)
- Map-controlled thermostat (electric heater)
- Intake camshaft adjuster, bank 1
- Intake camshaft adjuster, bank 2
- Exhaust camshaft adjuster, bank 1
- Exhaust camshaft adjuster, bank 2
- Coolant run-on pump (electric, for turbocharger)
- Tank vent valve
- Boost pressure adjuster, wastegate (2.0 l only)
- VTG turbocharger with integr. wastegate (2.5 l only)
- Engine mount switch-over valve
- Transmission mount switch-over valve
- Relay for electric fuel pump
- Control unit for demand-controlled fuel pump
- Tank leakage diagnosis DMTL (USA and South Korea only)
- Charge-air cooler 1 (EC fan)
- Charge-air cooler 2 (EC fan)
- Water pump 1, low-temperature circuit (ICAC)
- Radiator fan 1
- Radiator fan 2
- Quantity control valve 1 (Bosch HDP5)
- Oil pressure-regulating valve
- Valve, switched mechanical water pump
- Starter relay





# Group 3

## Power transmission



## 3 Power transmission

### 3.1 Introduction

The familiar manual and PDK transmissions are used for the 718 Boxster/S MY17. The details of the respective transmissions have been adapted for these models in each case.

### 3.2 Technical data


	Unit	Manual transmission	PDK (option)
<b>Transmission type (type code)</b>		G8200/G8220	CG210/CG240
<b>Vehicle</b>		718 Boxster/S	718 Boxster/S
<b>Clutch</b>		Single-plate dry clutch	2x radially nested multiple-disc wet clutches
<b>Number of gears, forward/reverse</b>		6/1	7/1
<b>Spread</b>		4.06	6.34
<b>Filling capacity</b>	l	3.2	3.2 + 5.4
<b>Weight (ready for installation)</b>	kg	69.85	110.5
<b>Additional weight of differential lock</b>	kg	0.55	2.8
<b>1<sup>st</sup> gear</b>	i	3.308	3.909
<b>2<sup>nd</sup> gear</b>	i	1.950	2.292
<b>3<sup>rd</sup> gear</b>	i	1.407	1.654
<b>4<sup>th</sup> gear</b>	i	1.133	1.303
<b>5<sup>th</sup> gear</b>	i	0.950	1.081
<b>6<sup>th</sup> gear</b>	i	0.814	0.881
<b>7<sup>th</sup> gear</b>	i		0.617
<b>Reverse gear</b>	i	3.000	3.545
<b>Rear-axle ratio</b>	i	3.889	3.250

Extract, data available at copy deadline, subject to change



<b>3.1</b>	<b>Introduction</b>	<b>65</b>
<b>3.2</b>	<b>Technical data</b>	<b>65</b>
<b>3.3</b>	<b>Manual transmission</b>	<b>66</b>
<b>3.3.1</b>	<b>Outer shift mechanism</b>	<b>66</b>
<b>3.3.2</b>	<b>Clutch</b>	<b>67</b>
<b>3.4</b>	<b>Porsche Doppelkupplung (PDK)</b>	<b>69</b>
<b>3.4.1</b>	<b>Technical data</b>	<b>70</b>
<b>3.4.2</b>	<b>Outer shift mechanism</b>	<b>70</b>
<b>3.4.3</b>	<b>Operating and display concept</b>	<b>71</b>
<b>3.5</b>	<b>Transmission mount</b>	<b>72</b>

### 3.3 Manual transmission




Manual transmission of the 718 Boxster/S MY17

3\_01\_17

The manual transmission of the 718 Boxster/S MY17 is based on the G8120 manual transmission used in the previous model.

#### 3.3.1 Outer shift mechanism



Shift lever connection and shift cable routing on the transmission of the 718 Boxster/S


3\_02\_17

Gearshifts are still performed using two shift cable mechanisms, which are guided from the gearshift bracket via the engine to the transmission.



## 718 Boxster/S Model Year 2017 (982)

On the manual transmission of the 718 Boxster/S MY17, both cables are routed over the engine between the air cleaner and integrated charge-air cooler.




Shift mechanism on manual transmission of 718 Boxster/S MY17

3\_03\_17

On the manual transmission in the 718 Boxster/S MY17, the right shift cable is connected to the transmission via an additional reversing lever (4) on the transmission housing.

### 3.3.2 Clutch



Single-plate clutch

3\_04\_17

- 1 Shift lever on shifting shaft
- 2 Coupling rod to shifting mass
- 3 Front reversing lever on transmission housing
- 4 Rear reversing lever on transmission housing
- 5 Shift cable support bracket
- 6 Pre-selector cable support bracket
- 7 Shift cable ring eyelets on ball pin
- 8 Attachment hose holders for shift cable in support bracket

- 1 Dual-mass flywheel
- 2 10x cheese head bolt
- 3 Clutch set
- 4 6x bi-hexagonal screw

## 718 Boxster/S Model Year 2017 (982)

Power transmission


# 3

The clutch pressure plate and driver plate have been adapted to the engine characteristics in order to reliably transfer the higher torque of the turbo engines. An adapted internal gear ratio ensures that the actuating forces are identical in spite of the reinforced diaphragm spring.

### Dual-mass flywheel

The dual-mass flywheel with integrated centrifugal pendulums familiar from the 911 Carrera/S MY17 is used on the 718 Boxster MY17. This was adapted for the flat-four engines.

The use of centrifugal pendulums significantly reduces torsional vibrations particularly in the low engine speed range, thereby improving driving comfort in the low-end rpm range.



- 1 Centrifugal pendulum
- 2 Arc springs (inner and outer)

Dual-mass flywheel with centrifugal pendulum

3\_05\_17

## 718 Boxster/S Model Year 2017 (982)


### Clutch slave cylinder

In order to minimise the effects of incorrect operation, e.g. foot slipping off the clutch pedal, a clutch slave cylinder with peak torque limiter (PTL) is installed in the 718 Boxster MY17. This extends the clutch engagement speed to at least 20 ms if necessary.

A movable valve disc is integrated in the hydraulic connection of the slave cylinder for this purpose. The valve disc moves against the cylinder housing when the clutch is disengaged. The clutch hydraulic fluid flows both through the bore in the valve disc as well as past the outside of the valve disc.

When the clutch is engaged, the valve disc moves against the disc cover and thus reduces the cross-section of the clutch line.

### 3.4 Porsche Doppelkupplung (PDK)




Porsche Doppelkupplung of the 718 Boxster/S MY17

3\_07\_17

The Porsche Doppelkupplung (PDK) of the 718 Boxster/S MY17 is based on the double-clutch transmission used in the previous model.



Power transmission



Peak Torque Limiter

3\_06\_17

- 1 Disc cover
- 2 Valve disc
- 3 Housing

## 718 Boxster/S

### Model Year 2017 (982)


Power transmission

3

#### 3.4.1 Technical data

<b>Gearshift positions</b>	P, R, N, D, M, +, -
<b>Selector lever</b>	Engaged in each gearshift position
<b>Selector lever lock</b>	<ul style="list-style-type: none"> <li>from P to R</li> <li>from R to P</li> <li>from N to R</li> </ul> Released by pressing the release button
<b>Gearshift lock (shift lock)</b>	In P and N Released by switching on ignition and actuating brake pedal
<b>Parking lock engagement/disengagement</b>	Via selector cable
<b>Transmission range engagement/disengagement</b>	Via vehicle electrical system/CAN
<b>Delta compared with previous model</b>	<u>Shifting direction</u> <ul style="list-style-type: none"> <li>Downshift (-) forward</li> <li>Upshift (+) back</li> </ul> <u>New design of selector knob</u> Without shift pattern on release button

#### 3.4.2 Outer shift mechanism



- 1 Attachment hose holder for cable
- 2 Cable eyelet on ball pin

Selector lever connection on PDK of 718 Boxster/S MY17

3\_08\_17



### 3.4.3 Operating and display concept



PDK selector lever 718 Boxster/S MY17

3\_09\_17

As on the 911 GT3 MY14 and the 911 Carrera MY17, the shift direction of the manual shift mechanism was also reversed on the 718 Boxster/S MY17. The selector lever is pushed forward to downshift and pulled back to upshift.



## 718 Boxster/S Model Year 2017 (982)


Power transmission

# 3



Sectional view of PADM transmission mount 3\_11\_17

### 3.5 Transmission mount



Unit mount

3\_10\_17

In addition to the conventionally designed transmission mount, PADM (Porsche Active Drivetrain Mount) is available as an option for the first time for the Boxster models. The two transmission mounts are replaced here by two active hydraulic mounts. The function and effect is the same as the PADM system used on the 911.



# Group 4 Chassis





## **4 Chassis**

### **4.1 Introduction**

As part of the continuous process of adapting the chassis of the Porsche 718 Boxster models to the increased customer wishes and sporting challenges, the following optimisations were implemented:


- The wheel width on the rear axle was increased by 0.5 inches compared with the previous model (with unchanged tyre size)
- The springs, dampers and anti-roll bars were also retuned to adapt them to the new chassis
- The speed-sensitive power steering is an enhancement from the Porsche 911 Turbo model year 2014 and is functionally extended with lane keeping assist
- The new sports steering wheel with the optional Sport Chrono package includes a Mode switch for selecting the different driving modes directly on the steering wheel
- The size of the brakes has been increased in line with the enhanced driving performance
- The PCCB of the 911 Carrera model year 2012 is optionally available for all models
- All models are equipped as standard with the third generation of the Tyre Pressure Monitoring system
- The software of the chassis control systems was adapted to the increased power of the new turbo engines
- All models can be optionally equipped with the cruise control system with braking intervention function
- The engine and transmission mounts were redesigned and are integrated in the proven PADM system

Chassis

4

<b>4.1</b>	<b>Introduction</b>	<b>75</b>
<b>4.2</b>	<b>Front axle</b>	<b>76</b>
<b>4.3</b>	<b>Rear axle</b>	<b>76</b>
<b>4.4</b>	<b>Power steering</b>	<b>77</b>
<b>4.5</b>	<b>Tyre Pressure Monitoring (TPM)</b>	<b>79</b>
<b>4.6</b>	<b>Wheels and tyres</b>	<b>83</b>
<b>4.7</b>	<b>Brakes</b>	<b>84</b>
<b>4.8</b>	<b>Control systems</b>	<b>86</b>

## 4.2 Front axle




Front axle

4\_01\_17

The wheel carriers, wheel hubs, wheel bearings and control arms were adopted from the 911 Carrera MY12 for the 718 Boxster MY17. In addition, the springs, dampers and anti-roll bars were retuned. The increased anti-dive characteristic reduces diving at the front of the vehicle during full braking and shortens the braking distance.

## 4.3 Rear axle



Rear axle


4\_02\_17

The Porsche-optimised MacPherson suspension used on the 718 Boxster models is essentially the same as the suspension used on the previous model. The springs, dampers and anti-roll bars were also retuned here.

#### 4.4 Power steering

Like the 911 Turbo MY14, the 718 Boxster MY17 models are also equipped with electromechanical power assistance for the steering. This has the following features and functions:

- Electromechanical power assistance
- Speed-sensitive steering torque control
- Steering pulse for  $\mu$ -split braking
- Power steering Plus (option)
- Lane keeping assist (option)



Steering gear

4\_03\_17

The direct steering in the 718 Boxster MY17 models was set up so that it is approx. 10% more direct than in the previous model. The electromechanical steering thus ensures even more agile and direct handling. The rear wheels have been made 0.5 inches wider for the same tyre size, thereby ensuring the stability typical for Porsche and also further enhancing precision.

	<b>718 Boxster (982)</b>	<b>Boxster (981)</b>
<b>Steering ratio (variable)</b>	15.0:1 (centre position) to 12.5	16.5:1 (centre position) to 12.37

The complete steering column, including adjustment function, has been adopted from the 911 Carrera MY12.







Chassis

4

4.4.1 Steering wheels

The design of the new sports steering wheel is based on that of the 918 Spyder steering wheel and, in combination with optional Sport Chrono package, includes a Mode switch for selecting the different driving modes directly on the steering wheel.

The GT sports steering wheel is available as an option. With a diameter of 360 mm, the steering wheel is 15 mm smaller than the standard sports steering wheel. This makes gives it an even more dynamic appearance and provides an even more direct steering feeling.

	Standard, optional: paddles	With multi-function & heating I-no. 489, optional: paddles	With Mode switch (Sport Chrono) optional: paddles, multi-function & heating
Sports steering wheel (Ø 375 mm)			
GT sports steering wheel (Ø 360 mm)			

The multi-function and steering wheel heating are also optionally available for all steering wheels.




## 4.5 Tyre Pressure Monitoring (TPM)

The third-generation Tyre Pressure Monitoring (TPM) system is used in the 718 Boxster MY17.

- Direct-measuring unidirectional TPM system
- Special TPM valves with installed wheel electronics (WE) (as for the generation 2.6 TPM in the 991)

### System overview



Overview of third-generation TPM

4\_05\_17

### 4.5.1 Wheel electronics

Wheel electronics units are installed on all four wheels. These wirelessly transmit all the required information to the TPM control unit. The compact wheel electronics units comprise several individual components:

- Valve
- Pressure sensor
- Temperature sensor
- Battery
- Voltage monitoring
- Transmitter



The wheel electronics units transmit their information only while the vehicle is moving. After extended idle periods, the pressure display only becomes active once the journey is started and the vehicle exceeds speeds of approx. 25 km/h (16 mph). See message in the instrument cluster.



The system can no longer actively interrogate the TPM Gen3 wheel electronics due to the omission of the transmitters in the wheel housings.

### **Wireless data transmission**

Wireless data transmission takes place at specified intervals. The following data is transmitted to the TPM control unit via the four wheel electronics units:

- Wheel sensor ID
- Measured tyre pressure
- Air temperature in the tyre
- Residual battery life of the wheel sensors

### **Transmission behaviour of the wheel electronics**

The wheel electronics units enter into energy-saving mode approx. 5 minutes after the vehicle journey has been completed and stop transmitting new data. Energy-saving mode can be ended by a change in tyre pressure of more than 0.1 bar. The wheel electronics start transmitting again after approx. 2 min.

#### **4.5.2 TPM control unit (compact control unit)**

The TPM control unit receives the radio signals from the wheel electronics, evaluates them and transmits the information to the instrument cluster, where the information can be displayed. It is equipped with an integrated antenna in order to receive the wireless signals.

### **Wheel positions**

The wheel positions are taught automatically through evaluation of the side and axle information.

### **Side determination**

During side determination, the directions of rotation of the individual wheels are determined by acceleration sensors in the wheel electronics.

### **Front and rear axle detection**

Front axle/rear axle detection is performed using different signal levels. These signal levels are determined by the different distances between the wheel electronics and the control unit with integral antenna, which is mounted off-centre on the front axle. The further the sensors are positioned away from the control unit, the lower the level of the transmitted signal.

Communication with the display instrument (instrument cluster) takes place via MMI CAN.

### **4.5.3 TPM operating and display concept**

The previous Porsche TPM operating and display concept has been retained as far as possible.

The required tyre pressures of all approved tyres to be monitored, load conditions and operating modes where applicable (standard/comfort pressure) are stored in the instrument cluster as previously.

### **Pressure display on instrument cluster**

All pressures are displayed at the end of the journey until the ignition is switched OFF (irrespective of the wheel electronics transmission mode)

If the ignition is switched ON again within approx. 10 minutes, all pressures continue to be displayed.

#### Service

It also remains possible to add additional tyres (e.g. Tequipment) including the required pressures at the free positions in the "Tyre type" menu by means of the PIWIS tester.

The TPM menu is entered directly by acknowledging the actual pressure display "Tyre pressure".

## 718 Boxster/S Model Year 2017 (982)

Chassis

# 4

The first level shows the TPM status with the configured tyre type to be monitored and its dimensions ("19" S"=19-inch summer tyres), the specifications for the selected load condition and – if available for selection – the mode (standard/comfort pressure).



Tyre pressure display




4\_06\_17 Fill info access

4\_07\_17

### Tyre pressure adaptation

A tick is set for "Comfort press." by clicking. If no tick is displayed, the standard pressure applies (up to  $v_{max}$ ).

The 2nd level is reached by confirmation of "Tyre type". Here it is then possible to select the approved tyres.



Example for tyre type

4\_08\_17



Pressure deviation display

4\_09\_17

### Service

The temperature-compensated pressure deviations (from the required pressure) are displayed in the 2nd level after confirming "Fill info".



## Teaching wheel set

- Vehicle is stationary for at least 5 minutes
- Installed tyre type selected in the TPM menu
- Message: "System learns from 25 km/h"
- Driving with  $v > 25$  km/h (16 mph)
- Ideally, drive without stopping until the pressures are displayed
- Learning time less than 2 min

The system only teaches the wheel electronics while the vehicle is moving. Stationary phases can extend the learning time significantly. Deviations from the teaching procedure described can lengthen the teaching time significantly. The teaching process is only completed UNSUCCESSFULLY if the message "Tyre pressure monitoring fault" is displayed.



Fault display

4\_10\_17



Wheel change display

4\_11\_17


### Message: "Wheel change detected"

The system is able to automatically recognise a wheel change or a change of the wheel electronics. The following message appears on the instrument cluster: "Wheel change detected".

## 4.6 Wheels and tyres

### 4.6.1 Wheels

The Carrera S wheel will be available in the option range of the 20-inch wheels. The wheel range now includes the 20-inch Carrera Sport wheel from Exclusive. The Carrera Classic wheel remains available.



Display after ignition ON

4\_12\_17



Carrera Classic wheel

4\_13\_17

The rear wheels of the Boxster models have been widened by 0.5 inches – with the same tyre size. This measure ensures stability in combination with the direct steering and further improves precision.

#### **4.6.2 Tyres**

A new generation of 18-, 19- and 20-inch summer tyres will be introduced for the 718 Boxster MY17 models. The new generation of summer tyres have extremely good dry handling characteristics, while the wet handling characteristics have also been improved.

A special rubber compound yields additional benefits for greater fuel economy. During the development of the summer tyres, engineers focussed on consistent lightweight construction, outstanding traction and driving stability, optimum driving comfort, low rolling resistance, an improved wear pattern and a long tyre service life.

#### **4.7 Brakes**

##### **4.7.1 Brake system versions for the 718 Boxster models**

The braking performance was adapted due to the higher engine power. The dimensions of the brake system have changed as a result.

The table below contains the dimensions of the individual brake discs on the 718 Boxster MY17 models:

<b>Derivative</b>	<b>Front axle</b>	<b>Rear axle</b>
<b>718 Boxster</b>	Ø 330 x 28 mm	Ø 299 x 20 mm
981 Boxster	Ø 315 x 28 mm	Ø 299 x 20 mm
<b>718 Boxster S</b>	Ø 330 x 34 mm	Ø 299 x 20 mm
981 Boxster S	Ø 330 x 28 mm	Ø 299 x 20 mm
<b>PCCB</b> (adopted from 991)	Ø 350 x 34 mm	Ø 350 x 28 mm

#### **4.7.2 Porsche Ceramic Composite Brake (PCCB)**

The optional Porsche Ceramic Composite Brake (PCCB) of the 718 Boxster MY17 models is equipped with brake discs with a diameter of 350 mm on the front and rear axles. The PCCB is available for all Boxster models and tyre sizes.

#### **4.7.3 Multi-collision brake**

The multi-collision brake is used as standard on the 718 Boxster model year 2017. If a collision is detected by this system, braking is initiated automatically with a maximum deceleration of 0.6 g to a speed of 10km/h (6 mph).

In the event of an accident, multi-collision braking can help the driver to reduce the risk of skidding and the danger of further collisions during the accident by initiating braking automatically.

##### Function

Multi-collision braking functions only:

- in the event of front, side and rear-end collisions
- if the airbag control unit detects a corresponding activation threshold during an accident
- if an accident occurs when the vehicle is travelling at a speed above approx. 10 km/h (6 mph)

The driver has the option of actively intervening in the braking process at any time and intensifying braking by actuating the brake pedal or interrupting braking by accelerating (accelerator pedal position > 90%).

Only software modifications in the existing PSM control unit and the airbag control unit are required to implement the function.

In the event of a collision, the multi-collision brake is triggered by a pulse from the airbag control unit. The activation threshold is coupled to the seat-belt pretensioner/airbag threshold.



PCCB brake disc

4\_14\_17



PSM automatically brakes the vehicle provided the hydraulic brake system, PSM and the electrical system are not damaged and are still working after the accident.



### Multi-collision

Only SW adaptation (use of airbag thresholds)

Trigger pulse

BUS

Build-up of brake pressure



### Multi-collision

Braking deceleration with 0.6 g  
to a speed of 10 km/h (6 mph)

Functional representation of the multi-collision brake

4\_15\_17

## 4.8 Control systems

### 4.8.1 Cruise control with braking intervention (Cruise control Plus)

When driving downhill, cruise control Plus can maintain the set cruise control speed by initiating automatic braking interventions. This is done by implementing a deceleration request of the DME (up to max. 0.1g). Cruise control constantly maintains any desired speed between approx. 30 – 240 km/h (20 – 150 mph). If "PSM off" is selected, the system is switched to "PSM on" when the target speed is set.



Trigger pulse

CAN bus

Digital  
Motor  
Electronics

Deceleration request

In case of speed deviation



Build-up of brake pressure



Overview of cruise control with braking intervention (cruise control Plus)

4\_16\_17

## Porsche Active Suspension Management (PASM)

The 718 Boxster models are optionally available with the electronically controlled Porsche Active Suspension Management (PASM) damper system with active and continuous control of the shock absorbers on the front and rear axles, including lowering of the vehicle height by 10 mm.

### PASM sports chassis (-20 mm)

The PASM sports chassis (-20 mm) is offered for the first time for the 718 Boxster models. In comparison with the PASM, the body is 20 mm lower, which lowers the vehicle centre of gravity even further. This has a positive effect on the driving dynamics capabilities of the vehicle in particular.

The PASM sports chassis (-20 mm) is optionally available for all 718 Boxster models.

### 4.8.2 Sport Chrono package

The Sport Chrono package for the 718 Boxster MY17 has been significantly modified.

#### Design

The various driving modes are now no longer selected using buttons on the centre console, but instead via a rotary selector switch known as the Mode switch located in the redesigned steering wheel. Individual mode is now available in addition to the three existing modes Normal, SPORT and SPORT PLUS.

#### Function

The settings for the PASM, sports exhaust system, auto start/stop function and rear spoiler can be combined individually based on Normal mode or SPORT modes via a corresponding menu in the instrument cluster.

The saved combination can be retrieved the next time the vehicle is started by turning the Mode switch to the I position.

With the Sport Chrono package, the standard SPORT button in the centre console is omitted. The stopwatch in the dashboard upper section remains part of the package.

## 718 Boxster/S Model Year 2017 (982)

Chassis

4



The 718 Boxster MY17 models have a chassis with zero position without PASM.

The chassis can be ordered with zero position with PASM for the Chinese market.



Steering wheel with Mode switch

4\_17\_17





Further information on the SPORT Response button can be found in Group 2.

### **Sport Response button**

Another new function in the Sport Chrono package is the SPORT Response button located in the centre of the Mode switch in conjunction with PDK.













The SPORT Response button on the 718 Boxster gives the driver the option of changing the responsiveness of the vehicle directly at the press of a button.

### **4.8.3 PSM Sport**


In conjunction with the Sport Chrono package, the Porsche Stability Management (PSM) system on the 718 Boxster models features a PSM Sport mode that can be activated separately. Briefly pressing the PSM button in the centre console sets the PSM system to a particularly sporty mode. In this mode, the ambitious driver can push closer to the limit range of the vehicle while remaining in a safe environment. However, PSM remains constantly active in the background.

PSM Sport mode can be activated independently of the selected driving mode. "PSM off" is activated as usual by a long press on the PSM button.

#### 4.8.4 Overview of Mode switch from Sport Chrono package (SCP)

 	Mode switch (Sport Chrono Package)					
	- 0 -	- S -	- S+ -	- I -	Sport Response button 	
	NORMAL 	SPORT 	SPORT PLUS 	INDIVIDUAL 		
					 for a maximum of 20 s	
Drive						
Engine management	Normal	Sport	Performance	Preselection	Selected mode	
Dynamic Boost	Normal	Sport	Performance	<b>Normal Sport Sport Plus</b>	0, S, S+ or I	
Accelerator pedal characteristic	Normal	Sport	Performance			
Idle speed increase	–	active	active			
Rev-limiter	Normal	Sport	Sport			
Intermediate throttle application for downshifts	–	active	active			
Backfire	–	active	–	Individual	Engine	
PDK shift characteristic	Normal	Sport	Performance	<b>Sport chassis</b> PASM Auto Start Stop Virtual gears Sports exhaust system Wing	<b>= Sport Plus</b>	
Launch Control	–	–	active			
Auto Start Stop	active	–	–			
Virtual gears	active	–	–			
Chassis						
Dynamic engine mounts	Normal	Sport	Performance			
PASM <sup>1)</sup>	Normal	Normal	Sport			
PSM	“PSM Sport” function via PSM button on centre console			Other	PDK	
Other					<b>= Preselection</b>	<b>= Sport Plus</b>
Dynamic cornering light	Normal	Sport	Sport	Normal	with shift characteristic	
Dynamic high beam (option) <sup>2)</sup>	Normal	Sport	Sport	or Sport or Sport Plus	Sport Response	
Adaptive cruise control (option) <sup>3)</sup>	Normal	Sport	Sport			
Sports exhaust system		active	active			
Rear spoiler	Speed-sensitive					
1) PASM program additionally adjustable individually via PASM button 2) Dynamic high beam only in conjunction with PDLS Plus (LED headlights) 3) In conjunction with the option adaptive cruise control incl. Active Safe (PAS)						

#### **4.8.5 Porsche Active Drivetrain Mount (PADM)**




Overview of dynamic engine mounts

4\_18\_17

The 718 Boxster MY17 models feature a 4-point drivetrain mount. The engine now has two switchable and vacuum-controlled engine mounts in comparison with the central engine mount of the previous model. The transmission mounts are designed as active hydraulic mounts for I-no. PADM (in combination with Sport Chrono).

##### Maintenance


The engine must be lowered by approx. 50 mm (measured at the engine mount pin) in order to removed the engine mounts. It is also not necessary to disconnect the coolant lines, so that there is also no need to drain, fill and bleed these lines.






# Group 5

## Body







## 5 Body

### 5.1 Introduction

When developing the 718 Boxster MY17 (982), it was largely possible to adopt the familiar Boxster MY12-16 (981) body.

The body front section, floorpan assembly and rear end were adopted virtually unchanged. Modifications here only affect individual holders or pins that were either added or relocated.

### 5.2 Comparison of technical data

	Unit	718 Boxster MY17 (982)	Boxster MY12-16 (981)
<b>Bodyshell weight (without add-on parts)</b>	kg	219	217
<b>cd value</b>	-	0.32	0.31
<b>Length</b>	mm	4,379	4,374
<b>Width (exterior mirrors folded in)</b>	mm	1,801	1,801
<b>Height (standard chassis)</b>	mm	1,281	1,282

Extract, data available at copy deadline, subject to change

The increase in weight of the bodyshell results in the following:

- 4-point mount: bearing brackets in carrier 3 for four-point engine mount
- Side section profile above the tail light.


### 5.3 Box-type bodyshell






The bodyshell of the 718 Boxster 982 is based on the bodyshell of the Boxster 981. Changes were required only in the following areas:

- Body front section: front end holder, battery box cross member, battery box
- Rear end: expanded foam part, bolt for shaker, engine mounting connection, rear wall, radiator reinforcement, crash reinforcement, shape of side panels

<b>5.1</b>	<b>Introduction</b>	<b>93</b>
<b>5.2</b>	<b>Comparison of technical data</b>	<b>93</b>
<b>5.3</b>	<b>Box-type bodyshell</b>	<b>93</b>
5.3.1	Body front section	95
5.3.2	Rear end	96
5.3.3	Add-on parts	97
5.3.4	Passive safety	99
5.3.5	Special tools & workshop equipment	100

## 718 Boxster/S Model Year 2017 (982)




-  Aluminium sheet
-  Extruded aluminium profile
-  Cast aluminium
-  Adopted from Boxster (981)
-  Deep-drawn steel

The same joining techniques are used. This means that the familiar flow-drill screws, high-strength blind rivets, MAG welding, spot welding and two-component body adhesive are still used in the event of repairs.

### Objective

The objective of bodyshell construction was to implement the new design while at the same time largely adopting the existing bodyshell. The basic structure of the box-type bodyshell has not changed here.



Box-type bodyshell of 718 Boxster MY17

5\_01\_17

### Design

The 718 Boxster models have the same body as that used for the Boxster 981 models in an aluminium/steel composite design. The idea behind this intelligent lightweight construction concept is use of “the right material in the right place”.

This means:

- Extensive use of aluminium to reduce the vehicle weight
- Use of ultra-high-strength steel for greater body rigidity and optimum passenger safety

## 718 Boxster/S Model Year 2017 (982)


### Repair

The repair concept was adopted in its entirety from the Boxster 981 models.

#### 5.3.1 Body front section

##### Design

In the body front section, the battery box cross member and the battery box itself have been modified. On the 718 Boxster MY17, these parts are designed as assembly parts and are bolted to the bodyshell.





Body front section 718 Boxster MY17

5\_03\_17

### Repair

The repair concept for the body front section is the same as for the Boxster 981 models. This means that in the event of structural damage that exceeds the specified bodyshell tolerance of the cast components of  $\pm 2$  mm, the luggage compartment liner or, depending on the further damage, the entire body front section must be replaced.








Battery box cross member

5\_02\_17

## 718 Boxster/S Model Year 2017 (982)




-  Aluminium sheet
-  Extruded aluminium profile
-  Cast aluminium
-  Adopted from Boxster (981)
-  Deep-drawn steel

- 1 Bracket for convertible top control unit
- 2 Bolt for shaker
- 3 Rear wall
- 4 Closed hole
- 5 Carrier 3 with four-point engine mount
- 6 Expanded foam part
- 7 Crash reinforcement

### 5.3.2 Rear end

#### Design

The rear end was mainly adopted from the Boxster 981. The changes affect the components listed in the diagram below.



Rear end 718 Boxster MY17

5\_04\_17

#### Repair

The repair concept for the rear end is the same as for the Boxster 981 models.

This means that in the event of structural damage that exceeds the specified bodysheet tolerance of the cast components of  $\pm 2$  mm, the entire rear end must be replaced.




### 5.3.3 Add-on parts

It was possible to adopt the front and rear lids from the Boxster 981 models. Consequently, it was only necessary to redevelop the doors and wings.

#### Doors

##### Design


The door shape was adopted from the Boxster 981 models. Since the finger plate has been omitted on the 718 Boxster models, the outer door panel and channel reinforcement have a modified cut in this area.



Comparison of outer door shell on Boxster 981 (left) with 718 Boxster 982 (right)


5\_05\_17

The door handle is integrated directly in the door outer shell, which is deep drawn at this point. The closing element is bolted to the outer door panel.



Door outer shell 718 Boxster MY17

5\_07\_16





Outer door handle and closing element  
 718 Boxster MY17

5\_06\_17


- 1 Handle recess on Boxster MY12-16
- 2 Handle recess on 718 Boxster MY17



## 718 Boxster/S Model Year 2017 (982)



Wing 718 Boxster MY17



Headlight connection

5\_10\_17

- 1 Headlight with retaining plate on Boxster MY12-16
- 2 Headlight without retaining plate on 718 Boxster MY17

## Wings

### Design

The shape of the wings was adapted due the modified front headlights. The connection concept corresponds to that of the Boxster MY12-16 models. The wings are still made of steel. However, the headlight retaining plate bolted to the wing is omitted, like on the 911 Carrera MY17 models.



5\_08\_17


### Repair

The repair concept is the same as for the Boxster 981 models.

## Headlight retaining plate


### Design

The xenon headlights no longer have a retaining plate, the main headlight housing is secured to the bodyshell directly by two screws and located in position by two pins.



1

Retaining plate



2

5\_09\_17

## Repair

The front apron must be detached to remove the headlights. The unlocking key is no longer included in the tool kit. The bulbs for the additional high beam must be replaced in the workshop.


### 5.3.4 Passive safety

#### Objective

The passive safety of a vehicle includes all measures that are taken to minimise the consequences of an accident. Various types of high-strength, super-high-strength and ultra-high-strength steel are used for this purpose on the 718 Boxster models. These materials are used in such a way in the vehicle that the impact created in an accident is routed through the bodyshell via defined load paths. The objective is to prevent any deformation or even destruction of the passenger compartment.

#### Design

The familiar fixed roll-over protection is used on the 718 Boxster. It consists of the roll-over bars, cross member and mountings.




- 1 Roll-over bar, left/right
- 2 Cross member
- 3 Mountings, left/right
- 4 Overall system

Roll-over protection 718 Boxster MY17

5\_11\_17

718 Boxster/S  
Model Year 2017 (982)



5.3.5 Special tools & workshop equipment

Special tools

Body repairs on the 718 Boxster MY17 are performed using the following:

- the Boxster 981 straightening set (VAS 6756A)
- the gantry attachment for the Boxster (VAS 5007/69)
- the measuring adapters of the electronic measuring system.


This equipment is set up and used in the same way as existing straightening benches for current vehicle models. It is manufactured by the familiar companies Car-o-liner and Celette.

Workshop equipment


The workshop equipment primarily comprises a body measuring and straightening system. Various options are available here. A detailed description of the approved tools can be found in PIWS. Only the most important workshop equipment is described briefly here.

The complete body straightening system package (V.A.G 1920) consists of straightening bench, straightening device with foot pump and accessory trolley.

The electronic measuring system (VAS 6527) is a further possibility for measuring and repairing the body.




Straightening system package V.A.G 1920 5\_12\_17



Electronic measuring system VAS 6527 5\_13\_17

Graphic	5_12_17	5_13_17
Order number	ASE 40645100000	ASE 40645600000
Purpose	Body repairs	



## **Group 6**

### **Body – Exterior equipment**





# 6 Body – Exterior equipment

## 6.1 Introduction

The future: Open as always. “Roadster dreams have always borne the name Porsche. The Porsche 356 No. 1 already followed this concept. We now launch the dynamic future of our mid-engine roadsters.” Legends of tomorrow. “The 550 Spyder was the ancestor of all super Sports Cars. Its successor, the 718, set standards on the race track. The 718 Boxster MY17 now follows this tradition. The Intelligent Performance maxim still holds as true today as it did then.” Less is more: Power. “Compact design combined with efficiency: the flat-four turbo engine achieves a quantum leap in performance. There is now no Boxster with less than 300 hp!”



718 Boxster MY17

6\_01\_17

In addition to the new generation of engines, the 718 Boxster has a much more striking design compared to the previous model, an even sportier chassis as well as a host of new performance, comfort and assistance systems. 718. The number that will make your heart beat faster.

# 718 Boxster/S Model Year 2017 (982)



Body –  
Exterior equipment

6.1	Introduction	103
6.2	Front	104
6.2.1	Front apron	105
6.3	Side view	106
6.3.1	Side skirts	107
6.3.2	Exterior mirrors	108
6.3.3	Doors	109
6.4	Rear	110
6.4.1	Rear apron	111
6.4.2	Rear spoiler	112
6.4.3	Rear lid	113
6.5	Roof systems	114

## 718 Boxster/S

### Model Year 2017 (982)

Body –  
Exterior equipment

6

The 718 Boxster MY17 remains compact, while its sharper lines lend the vehicle a much sportier design. The 718 Boxster has a very impressive look. It shows its strong character with greater precision of edges and curves. It is noticeably sporty due to its large wheels with snug wheel openings and short overhangs, clear dynamics and tight proportions due to emphasised air intakes, a low silhouette and a very flat elongated roof. In spite of a much sharper design, the 718 Boxster remains instantly recognisable as a Boxster.

#### 6.2 Front

The horizontal geometry of the air intakes makes the front appear even wider. The wings are positioned higher than the front bonnet and the design language of the wings emphasises the new headlight design, which incorporates an expressive interior and integral LED daytime running lights.



Front view


06\_02\_17

### 6.2.1 Front apron

#### Objective

The front apron of the 718 Boxster has a new impressive shape that is even more distinctive. The front section is flatter and the lines in the front apron lead outwards to make it appear wider from the front. The nose is lower and therefore gives the overall impression that the vehicle is closer to the ground.

The design edges in the top section of the front apron, which continue the contours of the V-shaped profile, are visually striking. This effect is supported by the narrow front light modules above the large side air intakes, which accommodate a position light and direction indicator.



Front apron 718 Boxster MY17

6\_03\_17

The centre part of the new front apron is characterised by two horizontal slats, which further emphasise the visual width of the 718 Boxster.

- 1 Front apron
- 2 Cover holder
- 3 Side light
- 4 Bumper wiring harness
- 5 Slat support
- 6 Tube for headlight cleaning system
- 7 Grille
- 8 Grille trim
- 9 Bracket cover
- 10 Parking assistant sensor
- 11 Direction indicator light
- 12 Spoiler lip
- 13 Centre grille

## 718 Boxster/S

### Model Year 2017 (982)

Body –  
Exterior equipment

# 6

The much larger air intakes on the front impressively visualise the new turbo engine concept on the outside.

#### Repair

The connection points joining the front apron to the bodyshell are the same as those on the Boxster 981 models.

### 6.3 Side view

In the side view, the 718 Boxster MY17 models captivate through their unmistakable flyline and new design incorporating mirrors, wings, doors, air intake trim and sill cover drawn with greater precision. The new mirrors are fitted with a V-shaped base and complement the sporty overall appearance of the 718 Boxster. The new door handles are another detail. They do not have a separate finger plate. The handle area on the door appears more defined and harmonious as a result. The indent in the door and the more precisely drawn contour edge lead to redesigned air intake with 2 slats. The enlarged air intake trim also visually emphasises the increased power of the 718 Boxster.




Side view

6\_04\_17

The fabric top of the 718 Boxster has a flat contour when closed, a feature typical of a Sports Car. The convertible top opens and closes fully automatically in 9 seconds at the push of a button – even when the vehicle is travelling at speeds up to 50 km/h (30 mph).

### 6.3.1 Side skirts

The basic shape of the side skirts has been adopted from the Boxster MY12-16 (981) models. The new trim for the air intake on the 718 Boxster models has two cross bars. The sill cover has a clearly visible contour edge that brings the vehicle visually closer to the road. The vehicle also appears lighter in the centre as a result.



Side skirts

6\_05\_17

#### Repair

The connection concept corresponds to that of the Boxster 981 models. The retaining strips are screwed onto the bodyshell and the side skirts are then clipped into position.

- 1 Side skirts
- 2 Air intake trim
- 3 Retaining frame trim
- 4 Front retaining strip
- 5 Door entry guard
- 6 Inner air duct
- 7 Retaining strip, centre
- 8 Side air guide
- 9 Upper part of air guide
- 10 Rear retaining strip



Air intake trim

6\_06\_17



## 718 Boxster/S Model Year 2017 (982)

Body –  
Exterior equipment


# 6

- 1 Mirror housing
- 2 Reinforcing plate incl. spring
- 3 Mirror glass
- 4 Glass adjustment drive
- 5 Wiring harness
- 6 Courtesy lighting
- 7 Housing cover
- 8 Seal
- 9 Mirror base covers
- 10 Mirror base
- 11 Seal

### 6.3.2 Exterior mirrors

#### Design

The functions of the exterior mirrors correspond to those of the 981 Boxster models. The exterior mirrors have a V-base design and, for the first time, an electric folding function. The upper part is painted in the body colour, while the lower part is a black grained plastic component.



Exterior mirror 718 Boxster MY17

6\_07\_17

#### Repair

The repair concept provides for replacement of the following components:

- Mirror base
- Mirror housing
- Mirror glass
- Glass adjustment drive
- Seals
- Courtesy lighting
- Wiring harness
- Housing cover
- Reinforcing plate including spring




Exterior mirror 718 Boxster MY17

6\_08\_17

### 6.3.3 Doors

#### Design

The basic door shape was adopted from the Boxster 981 models. The doors have been adapted in the area around the finger plates through the redesigned door handles. The supporting bows have also been redesigned.



Catch bar 718 Boxster MY17

6\_09\_17


#### Repair

The supporting bow is supplied as a spare part with a pre-fitted bowden cable – the bowden cable is also available separately and can be replaced individually. To facilitate assembly, the supporting bow is first clipped in and then screwed into position. Assembly is therefore easier compared to the Boxster 981 models. Seals and hardware accessories are available separately as spare parts. The repair concept is the same as for the Boxster 981 models. KESSY handles are primed as a spare part and supplied with built-in KESSY sensor. The handles are painted in an assembled state.

## 718 Boxster/S Model Year 2017 (982)


Body –  
Exterior equipment

6



Door handle without KESSY  
on 718 Boxster MY17

6\_10\_17



Door handle with KESSY  
on 718 Boxster MY17

6\_11\_17

- 1 Supporting bow
- 2 Base
- 3 Holder

## 718 Boxster/S

### Model Year 2017 (982)

Body –  
Exterior equipment

# 6

#### 6.4 Rear

The rear end of the 718 Boxster MY17 seems even more dynamic and wider. The feature that stands out on the rear end of the 718 Boxster is the trim strip with integral Porsche logo between the tail lights, which makes the vehicle seem much wider. The completely redeveloped tail lights also catch the eye immediately. The three-dimensional technology in the inner part is visible through the clear glass lens. The night design impresses with sharp, homogeneous tail light and brake light graphics.



Rear view


06\_12\_17

The reversing lights are integrated in the four lower brake light fingers. The tailpipes for the new exhaust systems are also located at the rear. As usual, the 718 Boxster models have one single-tube tailpipe, while the 718 Boxster S models are fitted with one twin tailpipe, which also visually suggests the higher engine performance. Their design has only been slightly adapted in order not to risk their recognition value as typical Porsche design elements. The wing located above is extended automatically at 120 km/h (75 mph) to reduce lift and improve road holding.

### 6.4.1 Rear apron

#### Design

The rear bodywork is now more sharply defined. The additional edge at the same height as the reflectors ensures that the vehicle looks significantly wider, commanding an appearance of even greater superiority. The diffuser is positioned higher and the enlarged black surface makes the rear end seem lighter.



Rear apron

6\_13\_17

#### Repair

The connection and repair concept was adopted from the Boxster 981 models.

- 1 Wiring harness for rear apron
- 2 Holder
- 3 Rear apron
- 4 Upper cover
- 5 Cable holder
- 6 Reversing camera
- 7 Rear fog light, reflector
- 8 Trim strip
- 9 Trim incl. logo
- 10 Heat shield, tailpipe

## 718 Boxster/S Model Year 2017 (982)

Body –  
Exterior equipment

# 6



Spoiler blade connection

6\_14\_17

- 1 Rear spoiler drive unit
- 2 Drive unit bolted connection
- 3 Drive unit connection to bodyshell



The spoiler must be extended before the upper part of the spoiler can be removed. If the drive malfunctions, the emergency release familiar from the previous models can be performed.


### 6.4.2 Rear spoiler

#### Objective

To optimise the drag coefficient and increase the contact pressure on the rear axle at higher speeds, all 718 Boxster models are fitted with an electrically retractable rear spoiler. The rear spoiler was largely adopted from the Boxster 981 models.

#### Design


The drive corresponds to that of the Boxster 981 models. It was also possible to adapt the connection concept to the bodyshell and mounting for the spoiler blade.



Rear spoiler drive for 718 Boxster MY17

6\_15\_17

The rear spoiler blade is 20 mm wider than on the previous models.



Screw connection on upper part of spoiler blade on 718 Boxster MY17

6\_16\_17




## Repair

As on the previous models, the spoiler upper and lower parts, drive unit and buffer stops of the kinematic system can be replaced.

### **6.4.3 Rear lid**

#### Design

The rear lid corresponds to that of the Boxster 981 models. There are changes only in the area of the raised brake light, which has a new lighting concept. The connection to the rear lid is realised by means of two screw points. As on the Boxster 981 models, the sealing concept includes three bonded-on seals. The trim is bonded directly to the brake light housing.




## Repair

The repair concept for the rear lid and the raised brake light corresponds to that of the Boxster 981 models.


**Body –  
Exterior equipment**

**6**



Raised brake light

6\_18\_17



Brake light trim

6\_19\_17

- 1 Housing
- 2 Plate
- 3 Light guide
- 4 2-component cover
- 5 Pin
- 6 Seal

## 718 Boxster/S Model Year 2017 (982)

Body –  
Exterior equipment

# 6

- 1 Insert
- 2 Synchronisation control unit

### 6.5 Roof systems

#### Design

The convertible top on the Boxster 981 models was completely adopted for the 718 Boxster MY17 models. The only change is in the position of the synchronisation control unit. The unit is no longer installed centrally on the rear bulkhead to the interior of the luggage compartment but is bolted to the inside of the right wheel arch.



Installation position of synchronisation control unit

6\_20\_17



Synchronisation control unit

6\_21\_17

#### Repair

The repair concept for 718 Boxster MY17 convertible top is the same as that of the Boxster 981 models.



# **Group 7**

## **Body – Interior equipment**



## 7 Body – Interior equipment

### 7.1 Introduction

Intuitive handling, performance-oriented ergonomics, clear design. The interior of the 718 Boxster MY17 is also designed entirely for sporty driving. A strong emphasis on horizontal lines lends the new dashboard design an imposing look, while retaining the usual high Porsche ergonomic standards: the elevated centre console shortens the distance between the steering wheel and the gear/selector lever. The clear arrangement of the function buttons saves time. Pure motor racing: the new sports steering wheel was derived from the 918 Spyder. The optional GT sports steering wheel with a smaller diameter further enhances the cockpit feeling.



Interior of 718 Boxster

7\_01\_17

The three round instruments with a central rev counter and 4.6 inch colour screen are typical of a Boxster. The fundamentally new Porsche Communication Management (PCM) system with 7-inch multi-touch screen with high-quality glass surface blends perfectly into the centre console.

**Body –  
Interior equipment**

**7**



- Diameter of sports steering wheel with 918 mm Spyder design: 375 mm
- Diameter of GT sports steering wheel: 360 mm

<b>7.1</b>	<b>Introduction</b>	<b>117</b>
<b>7.2</b>	<b>Trim panels, storage facilities and luggage compartment</b>	<b>118</b>
<b>7.2.1</b>	<b>Trim panels</b>	<b>118</b>
<b>7.2.2</b>	<b>Storage facilities</b>	<b>119</b>
<b>7.3</b>	<b>Operating and display concept</b>	<b>120</b>
<b>7.3.1</b>	<b>PDK cover</b>	<b>120</b>



### **Seat systems**

The seat system for all models was completely adopted from the Boxster 981 MY12-16 models.

### **Trim panels, storage facilities and luggage compartment**

The trim panels, storage facilities and luggage compartment were largely adopted from the Boxster 981 models. Changes affect the following areas:

- Dashboard upper section
- Dashboard air vents

### **Passive safety systems**

All passive safety systems were adopted from the Boxster 981 models.

### **Operating and display concept**

The operating concept is essentially the same as that of the Boxster 981 models.

## **7.2 Trim panels, storage facilities and luggage compartment**

### **7.2.1 Trim panels**

#### Design

Apart from the dashboard upper section, it was possible to adopt all trim panels from the Boxster 981 models.



7\_02\_17

## 718 Boxster/S Model Year 2017 (982)

The air vents are also new and lend the dashboard an even more striking appearance.

### Repair

The connection concept of the dashboard upper section corresponds to that of the Boxster 981 models.

### 7.2.2 Storage facilities


#### Design

As already familiar from the 911 Carrera MY17, the 718 Boxster MY17 also has a raised storage compartment.

#### Function


The reason for the raised position is the connection box installed in the centre console. The connection box is used for connection of a mobile phone and offers the following advantages:

- Dedicated mobile phone tray with charging function
- Improved reception and voice quality thanks to the use of an external antenna; also additional reduction in radiation in the passenger compartment
- Battery-saving operation




Connection box

7\_05\_17



Air vents

7\_03\_17



Centre-console storage bin

7\_04\_17

- 1 Mobile phone tray
- 2 USB socket

- 1 Connection box
- 2 Centre console tray



Detailed information on the function of the connection box is provided in Group 9.

## 718 Boxster/S Model Year 2017 (982)

Body –  
Interior equipment

# 7



Information on the MIB can be found  
in Group 9.

### 7.3 Operating and display concept

The operating and display concept was adopted from the Boxster 981 models. Changes have been implemented in the following areas:

- Modular infotainment kit (MIB)
- Trim/selector lever operation

#### 7.3.1 PDK cover

##### Design

The basic structure of the PDK cover was adopted from the Boxster 981 models. Like the GT vehicles from these model years, the shifting direction “+” of the manual gate has been moved to the rear.



Shift gate

7\_06\_17

The logo for the model designation across all models has also been standardised to “718”.



## Group 8

# Heating and air conditioning





## 8 Heating and air conditioning

### 8.1 Introduction


Like its predecessor, the 718 Boxster MY17 offers two-zone climate control, which continues to meet the highest demands in terms of comfort. At the same time, the average power consumption of the refrigerant compressor has been reduced and the overall performance of the air conditioner improved. This leads to faster response of the air conditioning system as well as a reduction in engine fuel consumption and emissions.

In order to meet the current legal requirements (EU directive 2006/40/EC) and the goals for “reduction of fluorinated greenhouse gases”, the new refrigerant R1234yf is used for the first time at Porsche – in the 718 Boxster. R1234yf will be used in the entire European region (EU28 countries). In addition to the USA, other markets outside the EU countries will also receive the refrigerant R1234yf. The refrigerant R134a will continue to be used in the other markets (RoW).

### 8.2 Control panel

The control panel for the OAU (Operating and Air-conditioning Unit) has been adopted from the predecessor model. The functionality and the operating logic remain unchanged.

The control unit integrated in the OAU regulates and controls all the heating and air conditioning system components. This also includes actuation of the newly added magnetic clutch of the electronically controlled A/C compressor (see section “Air-conditioning compressor”).



Compressor belt drive

8\_02\_17

<b>8.1</b>	<b>Introduction</b>	<b>123</b>
<b>8.2</b>	<b>Control panel</b>	<b>123</b>
<b>8.3</b>	<b>Refrigerant circuit</b>	<b>124</b>
8.3.1	System overview	125
8.3.2	Network topology	125
8.3.3	Air-conditioning compressor	126
8.3.4	Internal heat exchanger	127
8.3.5	Service connections	128


### 8.3 Refrigerant circuit



Refrigerant circuit – mid-engine concept

8\_01\_17

The refrigerant circuit essentially differs from the predecessor model only through the use of an electronically controlled A/C compressor with a magnetic clutch and swash plate. Furthermore, an IHE (Internal Heat Exchanger) is used in conjunction with optimised line routing.




Compressor position in engine compartment

8\_03\_17

A new refrigerant oil is also used in conjunction with the introduction of the new refrigerant (R1234yf). This oil must not be mixed with other oils or lubricants.


### 8.3.1 System overview



Schematic diagram of refrigerant circuit

8\_04\_17

### 8.3.2 Network topology



Block diagram

8\_05\_17


- 1 Compressor
  - 2 Condenser
  - 3 Filter dryer
  - 4 Internal heat exchanger (IHE)
  - 5 Expansion valve
  - 6 Evaporator
- HP High pressure  
 LP Low pressure

- DME DME control unit  
 OAU Operating and Air-conditioning Unit  
 (air-conditioning system control unit)  
 BCM Body control module, front
- 1 Evaporator temperature
  - 2 Refrigerant pressure (high pressure)
  - 3 Passenger compartment temperature
  - 4 Magnetic clutch (compressor)
  - 5 Control valve (compressor)
- AC Refrigerant compressor

#### CAN Data

- Drive CAN Drive  
 Comfort CAN Comfort  
 MMI CAN Man Machine Interface

### 8.3.3 Air-conditioning compressor



Compressor with magnetic clutch and control valve

8\_06\_17

The A/C compressor can be activated and deactivated via a magnetic clutch. The refrigerant delivery rate can be adjusted in the A/C compressor by actuation of the swash plate located in the compressor.

#### Function

Like the control valve, the magnetic clutch is actuated by the OAU.

Control of the A/C compressor is performed as a function of the following main input variables:

- **DME**
  - Engine load: torque request by driver
- **BCM**
  - Load management: generator load and vehicle electrical system voltage
- **OAU (sensors)**
  - Evaporator temperature (target/actual)
  - Desired interior temperature
  - Actual interior temperature
  - Refrigerant pressure (HP)



The evaporator temperature is the main input variable used for control of the solenoid valve and consequently of the swash plate position.

## Magnetic clutch

The magnetic clutch ensures that the A/C compressor can be fully switched off. The compressor then no longer causes drag torque. This improves engine responsiveness when torque is requested by the driver and reduces fuel consumption.

### Design

The magnetic clutch of the electronically controlled compressor features an aluminium solenoid coil winding. This reduces the weight of the magnetic clutch and therefore of the complete A/C compressor. The required power consumption is also lower than would be the case with conventional copper windings. Owing to the optimised design of the magnetic clutch and its windings, a lighter belt pulley mount is possible. This benefits the running smoothness of the compressor in conjunction with the new torsional vibration dampers.

### 8.3.4 Internal heat exchanger

#### Function


The task of the internal heat exchanger (IHE) is to exchange heat between the high-pressure and low-pressure sides (HP/LP). This takes place via a dual-pipe aluminium profile. The refrigerant under high pressure is routed into the centre of the dual-pipe profile. The refrigerant under low pressure is routed into the outer line structure of the pipe profile.

The refrigerant in the high-pressure side transfers heat to the refrigerant in the low-pressure side. The temperature of the refrigerant downstream of the condenser, i.e. upstream of the evaporator (HP), drops. The relative efficiency of the evaporator increases. Overall, this results in reduced fuel consumption.

## 718 Boxster/S Model Year 2017 (982)


### Heating and air conditioning

# 8



8\_07\_17

- 1 Solenoid coil made of aluminium (Al coil)
- 2 Leaf spring for magnetic clutch
- 3 Torsional vibration damper
- 4 Belt pulley mount



Design of IHE

8\_08\_17

- 1 Low-pressure side (LP)
- 2 High-pressure side (HP)



## 718 Boxster/S Model Year 2017 (982)

Heating and air conditioning

8



Grey covers of the service connections =>  
R1234yf refrigerant

Black covers of the service connections =>  
R134a refrigerant



Due to the increase in the average compressor temperature, free air flow to the A/C compressor must be checked and ensured during servicing.

- 1 Low-pressure connection (coded)
- 2 High-pressure connection (coded)
- 3 Internal heat exchanger (IHE)
- 4 High-pressure sensor

Further advantages include:


- Improvement of efficiency and performance of the system
- Any remaining fluid is re-evaporated in the IHE
- Improved compressor lubrication
- Increase in the average compressor temperature
- Increase in the cooling output
- Reduction in energy consumption of compressor
- Reduced engine CO<sub>2</sub> emissions

### 8.3.5 Service connections

Different refrigerants (R1234yf or R134a) are used in the 718 Boxster MY17 depending on the country version. This requires different service connections. In order to avoid confusion, the service connections are mechanically coded depending on the refrigerant used and the covers have different colours.

#### Installation position

Like on the previous model, the service connections are located close to the housing for fresh air (intake tube with pre-filter).




LHD vehicle

8\_09\_17

## 718 Boxster/S Model Year 2017 (982)

Heating and air conditioning

8



RHD vehicle

8\_10\_17

- 1 Low-pressure connection (coded)
- 2 High-pressure connection (coded)
- 3 Internal heat exchanger
- 4 High-pressure sensor

# Group 9

## Electrics and electronics



## 9 Electrics and electronics

### 9.1 Introduction

The electrical equipment of the 718 Boxster MY17 is enhanced and modified with each model. The main modifications relating to Group 9 are as follows:


- New functions, systems compared with the predecessor
- Changes to the lighting, new LED headlight, new tail lights, new attachment concept for the headlights
- New functions on the multi-function display of the instrument cluster
- Heatable washer jets omitted
- New Group door handle
- Use of PCC/PVTS functions via Apple Watch
- Lane Change Assist 3
- Emergency call system (Era-Glonass)
- New functions with the Sport Chrono option (Individual/Sport Response)
- New infotainment system Porsche Communication Management/PCM4
- MOST 150
- Other new infotainment functions
- Porsche Connect, backend and app-based services

### 9.2 Network topology

Various data bus systems (CAN 500 kBit/s, LIN 20 kBit/s, MOST 150 MBit/s) are used in the network of the 718 Boxster/S MY17. The gateway control unit serves as a central linking element and allows data exchange as well as protocol-dependent translation of communication between the various networks and bus technologies.

Electrics and electronics

9



Adaptive cruise control

9\_02\_17

<b>9.1</b>	<b>Introduction</b>	<b>131</b>
<b>9.2</b>	<b>Network topology</b>	<b>131</b>
<b>9.3</b>	<b>Vehicle electrical system/ energy management</b>	<b>134</b>
<b>9.4</b>	<b>Lighting</b>	<b>134</b>
<b>9.5</b>	<b>Instrument cluster</b>	<b>142</b>
<b>9.6</b>	<b>Wash/wipe systems</b>	<b>143</b>
<b>9.7</b>	<b>Door handles</b>	<b>143</b>
<b>9.8</b>	<b>Porsche Car Connect (PCC)</b>	<b>143</b>
<b>9.9</b>	<b>Porsche Vehicle Tracking System Plus (PVTS Plus)</b>	<b>144</b>
<b>9.10</b>	<b>Driver assistance systems</b>	<b>146</b>
<b>9.11</b>	<b>Era Glonass emergency call system</b>	<b>149</b>
<b>9.12</b>	<b>Sport Chrono package</b>	<b>150</b>
<b>9.13</b>	<b>PCM 4</b>	<b>152</b>
<b>9.14</b>	<b>Sound systems</b>	<b>162</b>
<b>9.15</b>	<b>Porsche Connect</b>	<b>164</b>
<b>9.16</b>	<b>Abbreviations</b>	<b>169</b>



## 718 Boxster/S Model Year 2017 (982)

Electrics and electronics

9


MOST 150 technology is used with the introduction of PCM4. This connects the digital amplifier/digital TV tuner components.



9\_03\_17

MOST 150 connects PCM4 to the optional/digital amplifier and/or the optional/digital TV tuner. The display and control unit (ABT) is connected to PCM4 via an internal PCM CAN (Private CAN).

In addition, the gateway control unit centrally controls all vehicle bus communication with respect to power-down/sleep mode for ignition/terminal 15 "off" in accordance with the rules defined in the "Vehicle Network State Manager".



9\_06\_17




## 718 Boxster/S Model Year 2017 (982)

Electrics and electronics

9


The gateway also assists fault finding using PIWIS Tester II and PIWIS Tester III by providing comprehensive system and diagnostic functions for monitoring network communication.

The gateway control unit also provides vehicle electrical system/vehicle energy management functions as an additional function. These functions support optimisation of battery charging during driving as well as minimisation of the closed-circuit current by switching off comfort functions and networks when the vehicle is stationary.



Overview of the network topology of the 718 Boxster/S MY17

9\_07\_17



Tail light

9\_08\_17

### **9.3 Vehicle electrical system/energy management**

The vehicle electrical system components comprising the battery sensor, main fuse box, generator and DC/DC converter are connected via the LIN bus connected directly to the gateway. The master function is stored in the gateway and is also used for diagnosis, maintenance and coding using a diagnosis tester. The vehicle electrical system/energy management functions are based on the functions from the predecessor 981, specifically:

- AGM battery (maintenance-free)
- External charging/jump starting as well as external voltage supply/emergency power supply
- Battery sensor
- Power distributor/main fuse box, installation positions of the relays/fuses
- Vehicle electrical system recuperation/coasting/Auto Start Stop/DC/DC converter

### **9.4 Lighting**

Three headlight variants are available for the 718 Boxster MY17 models. The standard equipment is a variant with Bi-Xenon headlights for dipped beam and high beam with a daytime running light module consisting of two LEDs. The control unit for the front-end electronics/BCM front is the master control unit for the lighting functions.



9\_09\_17

The second optional variant is a Bi-Xenon headlight with advanced frontlighting system (AFS), an LED additional high beam and a daytime running light module with 4 LEDs.



9\_10\_17

A full-LED headlight with the functions of the 4-LED daytime running light module, LED additional high beam, dynamic cornering light and continuous headlight range control is available as a third variant for the first time in the Boxster models.



9\_12\_17

#### **9.4.1 Headlight attachment concept**

The attachment concept for the headlights on the 718 Boxster MY17 has changed compared with the predecessor. They no longer have a retaining plate for unlocking the headlights, instead the headlight housings are screwed directly onto the bodyshell. The tool kit no longer contains an unlocking key for unlocking the headlight retaining plate. The front apron must now be detached to be able to access the screw connections to remove the headlights.

Electrics and electronics

9



Combination light

9\_11\_17



We recommend having bulbs replaced in the workshop due to the increased assembly work required.

## 718 Boxster/S Model Year 2017 (982)

### Electrics and electronics

# 9



Replacing light-emitting diodes and long-life bulbs:

- Note: Increased assembly work required!
- See Driver's Manual/Workshop Manual for instructions!
- Unlocking key no longer included in tool kit!




Instructions on how to remove the headlight can be found in the Workshop Manual (PIWIS information system/Driver's Manual).




H9 halogen bulb

9\_17\_17



9\_13\_17



9\_14\_17

### Repair

After headlight replacement/control unit exchange (Xenon/automatic headlight beam adjustment/LED), initial headlight configuration **must** be performed with the PIWIS Tester II! Owing to the modified attachment concept, the halogen additional high beam light must be repaired in a qualified workshop.

- Xenon main headlights no longer have a retaining plate
- The main headlight housing is screwed directly to the bodyshell
- The front apron must be detached to remove the headlights
- The unlocking key is no longer included in the tool kit
- Bulbs for the additional high beam light must be replaced in a workshop

### 9.4.2 25 W Bi-Xenon

A 25 W Bi-Xenon headlight previously used on the predecessor 981 is installed as standard. The headlight is equipped with a daytime running light module with reflector technology. A D8S Xenon bulb is used for the dipped beam and high beam. However, the bulb should be replaced in a qualified workshop due to the use of a new attachment concept for the headlights. The additional high beam is designed as a halogen high beam light with an H9 halogen bulb.



9\_15\_17

### Headlight functions

- Daytime running light module with reflector technology, 2 LEDs
- Dipped beam, Xenon high beam, D8S bulb
- Additional high beam/H9 65 W halogen high beam

#### 9.4.3 35 W Xenon headlight with AFS

A 35 W Bi-Xenon headlight with AFS (**A**dvanced **F**rontlighting **S**ystem) is offered as an option. The daytime running light module consists of a lens system equipped with 4 LEDs. A D3S Xenon bulb is used for the dipped beam and high beam. The additional high beam is realised with two reflectors using LEDs.

## 718 Boxster/S Model Year 2017 (982)

Electrics and electronics

9



D8S 25 W bulb

9\_16\_17



D3S 35 W bulb

9\_18\_17





35 W Xenon headlight with AFS, option

9\_19\_17

**Headlight functions**

- Daytime running lights with lens system, 4 LEDs
- Dipped beam, Xenon high beam, D3S bulb
- LED additional high beam (2 LEDs, 1x Osram 5 Chip, 2 reflectors)





**Main headlight functions**

	25 W Bi-Xenon	35 W Xenon with AFS	LED
Daytime running lights	2 LEDs	4 LEDs	4 LEDs
Additional high beam	X	LED	LED
Headlight beam adjustment		X	X
Dynamic cornering light		X	X
Continuous headlight range control			X

#### 9.4.4 Lighting functions

##### Light switch

The light switch has five switch positions for activating different functions. These switch positions are:

-  **Off** = Light switched off
- **AUTO** **AUTO** = Automatic headlights
-  Parking light
-  Dipped beam/driving light
-  Rear fog light

A distinction is made between lighting functions with:

- Ignition off
- Ignition on
- Light switch set to "AUTO"
- the four other light switch positions

A wide range of functions are available; the settings for them can be found in the Driver's Manual.

##### Standard lighting

The front light module is designed in LED light guide technology for the functions position light (1 LED) and direction indicator (4 LEDs). The side indicator light features the indicating/hazard warning functions (LED technology).



9\_23\_17

Electrics and electronics

9



Position light in front light module

9\_20\_17



Direction indicator light in front light module

9\_21\_17



Side indicator light

9\_22\_17


## 9.4.5 Rear lighting

### Tail light


The tail light features a new transparent design and 3D look. The attachment concept is the same as the predecessor.

### Lighting functions/light patterns



- Brake light: 4 points (12 LEDs), bar (52 LEDs)
- Tail light (52 LEDs)
- Direction indicator light (22 LEDs: yellow (ECE)/red (SAE))
- Reversing light (4 LEDs)



9\_24\_17



9\_25\_17




9\_26\_17

### Raised brake light


The raised brake light contains 48 LEDs.

### Emergency braking

If the vehicle is fully braked from a speed of more than approx. 70 km/h (43 mph), the brake light pulsates during braking.



9\_27\_17



9\_28\_17


- 1 Pin
- 2 Seal
- 3 Housing
- 4 Plate
- 5 Light guide
- 6 2-component cover

### Combination light

The combination light on the rear apron contains the functions of the rear fog light (on one side) and the reflector.

- Rear fog light (1 LED)
- Reflector

The combination light is mounted by means of two clips and one screw.



Combination light

9\_29\_17

## 718 Boxster/S Model Year 2017 (982)

### Electrics and electronics

# 9



Individual 9\_30\_17



ACC 9\_31\_17



Sport Response 9\_69\_17



Sport Plus 9\_34\_17




G-force 9\_35\_17



Chrono 9\_36\_17

## 9.5 Instrument cluster

The instrument cluster is the central driver information unit and is used to display data relating to the vehicle, e.g. engine speed, vehicle speed, temperatures and fill levels, warnings and messages.



Instrument cluster

9\_32\_17

General vehicle settings can be made in the instrument cluster by means of a selection menu and made available to the control unit network via CAN. The following vehicle information/menus can be displayed in the right-hand display area on the multi-function display:

- Vehicle
- Audio, Navigation
- Map, Phone
- Trip
- Tyre pressure
- Chrono
- Gear shift assist
- Maximum g-force
- ACC

The multi-function display contains advanced and/or new functions/menus compared with the previous model, including:

- Vehicle\Settings\Individual (Sport Chrono equipment option)
- Vehicle\Settings\Assist. Systems\PAS (adaptive cruise control option)
- Vehicle\Settings\Assist. Systems\LCA (Lane Change Assist option)
- Vehicle\Settings\Car Connect (Porsche Car Connect/PVTS option)
- ACC (option)



## 9.6 Wash/wipe systems

### 9.6.1 Windscreen washer system

The heatable washer nozzles have been omitted from MY17.

## 9.7 Door handles

The plastic finger plates of the door handles have been replaced with a deep drawn section in the outer door handle. The look thus conforms with the Group door handle. The handle is available in versions with and without capacitive sensors.



9\_38\_17




9\_39\_17

## 9.8 Porsche Car Connect (PCC)

The familiar components from the Panamera, Cayenne, Macan and 911 are now also used in the 718 Boxster MY17 for the introduction of Porsche Car Connect (Remote Services/PVTS).

The Porsche Car Connect smartphone app offers the option of establishing a wireless connection with the vehicle via a mobile phone (Apple/Android). This enables vehicle-specific information to be accessed directly via the smartphone and selected settings to be configured directly on the vehicle using the app. There are two vehicle versions available:

- Porsche Car Connect (Remote Service)
- Porsche Car Connect with PVTS Plus (Porsche Vehicle Tracking System Plus)



PCC registration

9\_42\_17



Apple Watch



9\_43\_17

## 718 Boxster/S Model Year 2017 (982)


### Electrics and electronics

9



Washer jet

9\_37\_17



9\_120\_17



9\_121\_17

718 Boxster/S  
Model Year 2017 (982)

Electrics and electronics

9

9.9 Porsche Vehicle Tracking System Plus (PVTS Plus)

PVTS Plus is a GSM/GPS-based tracking system that allows a control centre to locate the vehicle if it is stolen. It can then be found by the authorities. As soon as PVTS Plus detects a theft alarm, the location of the vehicle in question is sent to the SOC.

There are three different PVTS Plus equipment variants:

- PVTS Plus with driver card
- PVTS Plus with remote keypad
- PVTS Plus without driver card/without remote keypad

I-no.	Scope of supply	Driver card	Remote keypad	PVTS profile
7G9	PCC including PVTS WITHOUT security package	NO	NO	Belgium, Luxembourg: AUTONOMOUS RoW: COMFORT
7i0	PCC including PVTS WITH security package	NO	YES	Belgium, Luxembourg: INTEGRATED RoW: not available
7i2	PCC including PVTS WITH security package	YES	NO	Belgium, Luxembourg: not available RoW: ADVANCED




9\_43\_17



9\_122\_17



9\_123\_17



Customer portal registration

9\_47\_17

To use the smartphone app/Mobile Online Services (MOS) function, the customer must first apply for these services online by completing a registration process.

- The customer does this by creating a user account on the customer portal. A code is generated during this registration.
- The customer informs the Porsche Centre of this code.
- The Porsche dealer enters this first installation code in the Porsche diagnosis tester, which generates a second installation code.
- PPTS is now activated in the vehicle via the data processing centre/backend (Vodafone Automotive) by linking the first and second installation codes for the customer, vehicle and control unit.
- The dealer activates the mobile online services in front of the customer.
- The customer then receives a text message (SMS) that installation has been completed. The customer is also sent a link to the App Store together with the activation code for the application.

#### Diagnosis/commissioning

The following initial operation steps can be performed using the PIWIS II Diagnostic Tester:

Procedure:

- "PCC commissioning"
- "Teach PCC driver cards"
- "PCC function test"
- "Deactivate PCC"

## 718 Boxster/S Model Year 2017 (982)

### Electrics and electronics

9



Car Connect

Download in  
App Store

9\_48\_17




Car Connect


9\_49\_17



Customers can perform end-to-end diagnosis of the communication chain using the smartphone app.



9\_40\_17



9\_44\_17

## 718 Boxster/S Model Year 2017 (982)

### Electrics and electronics

9




LCA display

9\_53\_17



LCA3 control unit

9\_118\_17




9\_41\_17

## 9.10 Driver assistance systems

### 9.10.1 Lane Change Assist 3 (LCA)


Lane Change Assist will be introduced in the 718 Boxster MY17 for the first time. It uses two radar sensors at the right and left side of the rear bumper to monitor the lanes up to 70 metres behind the vehicle as well as the blind spot. Lane Change Assist thus enhances driving comfort/the warning function when driving on motorways in particular.



Lane Change Assist


9\_52\_17

If the system detects another vehicle in the adjacent lane or the blind spot, it informs the driver by displaying a visual signal (3 LEDs) in the mirror attachment point finisher. If the driver sets the direction indicator in this scenario, the warning stage information display flashes brightly as a clear warning about the approaching vehicle. The system is active in a speed range from 30 to 250 km/h (19 mph and 155 mph). It can be activated and deactivated via the on-board computer in the instrument cluster.



LCA settings

9\_45\_17



9\_46\_17

This display information is provided in two stages: as long as the driver does not set the direction indicator, the light unobtrusively and subtly signals detected vehicles in the neighbouring lanes.


Lane Change Assist decides whether to display the vehicle based on relative speed and distance. If the driver sets the direction indicator, the LEDs will inform him of the detected vehicle by flashing brightly.

LCA does not intervene in vehicle control and can be deactivated at any time by the driver via the multi-function display (Vehicle\Settings\Assist. Systems\LCA).

When LCA is activated via the multi-function display, both LED modules in the exterior mirrors briefly light up to provide visual feedback that the system is active. There is no system feedback when LCA is deactivated. The activation status of LCA can be seen via the function light in the instrument cluster/multifunction display. The basic brightness of the LED modules (information display) can be adapted to the driver's wishes in three brightness levels via a menu in the instrument cluster. The effective brightness of the information display depends on this basic setting and is adjusted in tandem with the current outside brightness. The range of the radar sensor is highly dependent on the weather conditions. Temporary unavailability due to dirt on the bumper and/or bad weather conditions (fog, spray behind the vehicle, etc) or a potential system malfunction are indicated via text messages in the instrument cluster and result in automatic deactivation of the system. The system can be reactivated by simply switching it back on manually.

#### Repair

"Re-calibration" is necessary after replacing a control unit or removing the rear apron (see Workshop Manual). Calibration is performed in the same manner as for the familiar systems, the measurement setup for calibration is described in the PIWIS information system and can be carried out using PIWIS Tester II. Coding of the control units is performed during the calibration process. The existing special tool (calibration unit VAS 6350, laser distance meter VAS 6350/2, Doppler generator VAS 6350/4, PIWIS Tester II) can still be used for calibration on the 718 Boxster MY17.




VAS 6350

9\_58\_17



VAS 6350/2

9\_59\_17



VAS 6350/4

9\_60\_17



## 718 Boxster/S

### Model Year 2017 (982)

#### Electrics and electronics

# 9



ACC control switch

9\_61\_17

#### 9.10.2 Adaptive cruise control (ACC)/cruise control (CRC)

##### Adaptive cruise control (ACC)

The optional adaptive cruise control on the 718 Boxster MY17 is essentially the same as the system on the previous model. It is installed in the front apron at the centre of the vehicle. One new feature is that the “coasting” function already familiar from the predecessor model is now available with the adaptive cruise control. This enables a considerable reduction in the fuel consumption.



ACC radar sensor

9\_62\_17

The distance to the vehicle in front is monitored using radar sensors. There is a radar sensor integrated in the front apron at the centre of the vehicle for this. ACC automatically maintains the distance to the vehicle in front or the desired speed and brakes smoothly if the distance to the vehicle in front is reduced, if necessary bringing the vehicle to a complete stop. The speed range can be individually adjusted and set between 30 – 210 km/h (19-130 mph). ACC is available as an option in combination with Porsche Doppelkupplung (PDK) and actively regulates the speed as a function of the distance to the vehicle in front. A radar sensor monitors the area up to 200 m in front of your vehicle in the same lane. If you approach the vehicle in front too quickly, Porsche Active Safe (PAS) warns you with an audible and visible signal. If necessary, there is a brief braking jolt and targeted braking is initiated – braking started by the driver is boosted within the system limits, right up to an emergency stop.

## Cruise control (CRC)

The optional cruise control for the 718 Boxster MY17 now brakes actively when the preset speed is reduced on the control stalk or the vehicle exceeds the preset speed when travelling downhill.

## 9.11 Era Glonass emergency call system

### (Global Navigation Satellite System)

As with the 911 Carrera MY17, an emergency call system for the Russian market (Era-Glonass) is now also installed in the 718 Boxster MY17 for the first time. The emergency call system does not require a registered mobile phone in the vehicle because it has its own independent mobile communications module (SIM card). If it is not possible to establish a connection to the emergency call centre, an emergency call is made to a public emergency number. In certain circumstances, it may not be possible to make an emergency call to the emergency call centre (e.g. no mobile phone network). If the vehicle battery is disconnected or faulty, an integrated battery (backup battery) ensures that the emergency call system is available for at least one hour. When the ignition is switched off, the emergency call can only be made by pressing the SOS button.

#### Automatic emergency call

A connection to the emergency call centre is established immediately after the airbag is triggered.

#### Data transmission

When an emergency call is made, any available data is transmitted to the emergency call centre to determine the rescue measures required. These may include:

- Current position of the vehicle
- Chassis number
- Vehicle type (e.g. hybrid vehicle)


## 718 Boxster/S Model Year 2017 (982)

### Electrics and electronics

# 9



Era-Glonass is a global navigation satellite system operated and financed by the Russian Ministry of Defence.



9\_63\_17

A/B Indicator/function lights

C SOS emergency call button under the cover


D Test emergency call button

## 718 Boxster/S Model Year 2017 (982)

### Electrics and electronics

# 9

- 1 Diagnostic socket (alternative)
- 2 Switch module + microphone
- 3 Control unit
- 4 Diagnostic socket
- 5 Loudspeaker



Era-Glonass components (example 991II)

9\_64\_17

### Diagnosis

A separate OBD diagnostic connection is provided for diagnosis of the Era Glonass system. The diagnosis connection is located in the passenger footwell on the fuse carrier (A-pillar). This can be connected with the vehicle OBD diagnostic connector by means of a Y-cable for system diagnosis with the PT2G/PT3G. The Y-cable is available as a special tool for Russia.

The Era-Glonass control unit is integrated into the diagnostic software as a control unit. The diagnostic scope will probably include the following:

- Identification
- Fault memory
- Measured values
- Procedure for commissioning the system
- Procedure for replacing the backup battery

Fault memory entries cannot be cleared; they become inactive once the fault has been rectified.

### **9.12 Sport Chrono package**

The Sport Chrono package is the first choice on the list of available options for increasing driving performance and driving pleasure. It was significantly redesigned for the 911 Carrera MY17 and is now also available as an option for the 718 Boxster MY17.



Steering wheel operation 9\_65\_17




Mode switch 9\_66\_17

### 9.12.1 Mode switch (in combination with PDK)


With the Sport Chrono option, five settings can be selected using the mode switch on the steering wheel:

- Normal (O)
- SPORT (S)
- SPORT PLUS (S+)
- Individual (I)
- Sport Response (centre button)


The settings for PASM, the sports exhaust system, Auto Start Stop function and rear spoiler can be combined individually based on Normal mode or SPORT modes via a corresponding menu in the instrument cluster/multi-function display. The saved combination can be retrieved the next time the vehicle is started by turning the Mode switch.



Sport Response display 9\_69\_17



9\_67\_17



Individual settings 9\_68\_17

## 718 Boxster/S Model Year 2017 (982)

### Electrics and electronics

9



9\_70\_17



9\_71\_17



9\_72\_17

### 9.13 PCM 4

Owing to the rapid developments in the field of multimedia applications, the challenges placed on vehicle manufacturers in order to keep up-to-date are growing. One example is the fact that many mobile phone manufacturers are updating their top models on an annual basis as well as continuously expanding their software. Vehicle users, in turn, want to connect their current mobile phones to the infotainment systems at any time. In order to meet the requirements of these rapid developments, the development cycles for automotive infotainment systems also have to become shorter. In recent years, the following changes have been implemented at Porsche:

PCM3/CDR30	Introduction in 2008 with the Carrera 997 II
PCM3.1/CDR31	Introduction in 2010 in the Panamera
PCM4	Introduction in 2015 in the 911 Carrera MY17

#### 9.13.1 Infotainment offering

Porsche Communication Management (PCM) with Sound Package Plus 150 W including mobile phone preparation (HFP) is standard on the 718 Boxster MY17

#### Options

- Navigation module including voice control
- Connect module, including smartphone tray, Porsche Connect and Apple CarPlay®
- Connect Plus module: (includes Connect module) including telephone module, wireless internet access, realtime traffic information (RTTI), online navigation module with Google StreetView® and Google Earth®
- Electronic logbook
- Digital radio/DAB
- TV tuner
- TV tuner including digital radio/DAB
- BOSE® Surround Sound System
- Burmester® High-End Surround Sound System




## 718 Boxster/S Model Year 2017 (982)

### Electrics and electronics


9

### 9.13.2 Features of the PCM 4

- Frameless display design
- 7-inch WVGA display
- Capacitive touchscreen with handwriting recognition (also available in Asia)
- DVD single drive, 2 SD slots, 1 SIM slot (under cover)
- Sound Package Plus, 150 W, integral analogue amplifier with digital sound processor



9\_74\_17



Jukebox

9\_73\_17


### 9.13.3 MOST connection

The infotainment system (PCM4) is connected to the vehicle via the MMI CAN in order to send e.g. displays to the instrument cluster or to exchange and display various vehicle settings. The central computer is connected to the Display and Control Unit (ABT) and forms one unit together with this (head unit). These components communicate via the internal PCM CAN. The analogue amplifier (Sound Package Plus) is not connected to the MOST ring as this is part of the central computer. The optionally available amplifiers (BOSE/Burmester) are connected via MOST 150, as is the optionally available TV tuner.



Integrated display and control unit (ABT)  
with central computer (head unit) of PCM4

9\_75\_17



9\_114\_17


### 9.13.4 Capacitive touchscreen with proximity detection

#### Capacitive touchscreen


The surface of a capacitive touchscreen consists of two glass panels positioned on top of one another. They are coated with strips of a transparent, conductive metal oxide. The glass panels are arranged such that the coated sides face one another and the strips form a grid. Electrically insulating spacers prevent the coatings from touching.

#### Function


(Figure 9\_77\_17) Each intersection point on the grid acts like a capacitor because the metal oxide strips are positioned exactly above one another, similar to capacitor plates. An electrical field forms between the strips when a voltage is applied to the two coatings (Figure 9\_78\_17). The intersection points therefore have a prescribed electrical capacitance, like a capacitor. When a finger touches the surface, for example, (Figure 9\_79\_17), the operator's electrical field influences the electrical field at the touched intersection point, as well as its capacitance. This results in a change in the voltages at the ends of the coating strips. The evaluation electronics uses this information to calculate the coordinates of the contact point on the touchscreen.



9\_79\_17




9\_77\_17




9\_78\_17

### Proximity detection




9\_80\_17



9\_81\_17


### Function

If a hand is moved inside the detection range of the infrared (IR) sensor strips (to the left and right of the display), the hand reflects the radiation emitted by the sensors back to the sensor strip. The reflected beam is then detected by the IR sensors. Following proximity detection, additional graphical operating elements appear on the PCM4 display.



Proximity detection

9\_82\_17



9\_83\_17


## 718 Boxster/S Model Year 2017 (982)

Electrics and electronics

9



Widget = A component on a graphic user interface



My Screen

9\_86\_17

### Handwriting recognition

Another new feature is the handwriting recognition feature of PCM. Instead of entering letters using the keypad, the user can now write letters directly onto the touchscreen to make it easier to enter e.g. addresses.



9\_84\_17




9\_85\_17

### 9.13.5 My Screen

The new “My Screen” function in the “Home” menu allows users to create a maximum of three personal screens using various widgets. Frequently used navigation destinations or telephone numbers, for example, can be stored on this screen and retrieved by simply touching the screen. If the user switches off PCM while the “My Screen” view is open, the same screen appears the next time the system is switched on again. Technically speaking, the “My Screen” function divides the screen into a maximum of eight fields to which various widgets can be assigned using drag and drop. The widgets can be positioned anywhere inside the fields, whereby some widgets occupy several fields.

### 9.13.6 Jukebox

The 11 GB jukebox in the new PCM also includes several new features.



Jukebox

9\_87\_17

Firstly, it synchronises MP3 files automatically using a database to display album covers and additional information about the music data stored. In addition to the maximum of two USB ports, music files can now be imported from an SD card inserted into one of the two SD interfaces under the PCM touchscreen or played back directly from the card. There is one USB interface in the oddments tray in the centre console. The second USB port is located in the glove box.

## 718 Boxster/S Model Year 2017 (982)

### Electrics and electronics

9



SD/SIM card slot under cover

9\_76\_17



USB/AUX interface

9\_88\_17




On vehicles with the Connect/Connect Plus option, the USB connection with Apple detection/Apple CarPlay function is in the centre console.




## 718 Boxster/S Model Year 2017 (982)

### Electrics and electronics

9




9\_89\_17



Mobile phone tray


9\_90\_17



9\_92\_17

### 9.13.7 Console for mobile phone in conjunction with mobile phone preparation

The console for mobile phones is integrated under the tray in the centre console. It provides the option of inductive/capacitive transmission of the mobile phone's RF signal via the mobile phone tray. This signal is then transferred to the 2-way amplifier (compensator), which forwards the signal to the external antenna in the (stick-on antenna in the front bumper). In the reverse case, the signal received from the external antenna is forwarded by the external antenna to the compensator; this transmits the signal to the mobile phone tray, which transfers the signal inductively/capacitively to the mobile phone.



9\_91\_17

### 9.13.8 Media playback

Music and video files from a wide range of media sources can be played by pressing the Media button. For the first time, DVD video files can be played from DVD and USB/SD memory cards in the following formats:


- Windows Media Audio 9 and 10
- Windows Media Video 9
- MPEG-2/-4, MPEG-1/-2
- ISO-MPEG4, DivX 3, 4 and 5, Xvid
- ISO-MPEG4, H.264 (MPEG4 AVC)

when the vehicle is stationary.

### 9.13.9 Antenna overview

The figure shows an overview of the most commonly used antennae in the 718 Boxster MY17. There are also further antennae for functions such as:


- Remote control (RC) in windscreen (LF/HF)
- Keyless Entry Start System (KESY) interior and exterior antennas
- Porsche Car Connect (PCC)/Porsche Vehicle Tracking System (PVTs) GSM/GPS
- Era Glonass emergency call system (GSM/GPS)



Antenna overview

### 9.13.10 MOST 150 data bus


The previous MOST 25 data bus has been replaced by the MOST 150 data bus for the infotainment system. MOST stands for “Media Oriented System Transport”, which is a serial data bus system for transmitting audio, video, voice and data signals via an optical waveguide. MOST 150 is present in the vehicle whenever a BOSE/Burmester digital amplifier or optional TV tuner is installed. The illustration on the right shows the components connected to the MOST ring. If a digital amplifier/TV tuner is not installed, the MOST ring is omitted from the vehicle. The display and control unit (ABT) is connected to PCM4/central computer via an internal PCM CAN.



MOST network

9\_93\_17

9\_94\_17



9\_115\_17


Prior to transmission, the data is divided into data packages, also known as frames. Each frame is 3,072 bits long in the MOST 150 data bus (MOST 25 = 512 bits). The length of the digital useful data is 3,040 bits (MOST 25 = 480 bits), which means that much more information is transmitted per data package in the MOST150. The total length of a frame consists of: one data field for administrative purposes, one data field for control data and two additional data fields. The maximum amount of data that can be stored in the two data fields is limited by these fixed divisions. The data is transmitted via three channels (control, synchronous and asynchronous channels): via the control channel for control data, via the synchronous channel for audio and video data transmission (synchronous real-time transmission without intermediate storage), and via the asynchronous channel for larger quantities of data, e.g. metadata of audio files (asynchronous, event-controlled data transmission, intermediate storage possible). The optical MOST150 data bus exchanges data between the relevant components in digital form. Data transmission using light waves enables a much higher data transfer rate. Light waves have extremely short wavelengths compared to radio waves. They do not generate electromagnetic interference waves and are also immune to interference from external electromagnetic influences.

#### 9.13.11 Wireless internet access – WLAN (Wireless Local Area Network)


WLAN is an abbreviation for “Wireless Local Area Network”. It refers to a wireless local network to which various devices such as handhelds, smartphones, tablet PCs or laptops can be connected to exchange data or obtain secure access to the internet.

An additional SIM card in the vehicle is the preferred method for establishing a WLAN connection, which means that a vehicle with WLAN offers an on-board internet access point (hotspot). WiFi-compatible end devices can connect to this hotspot in the vehicle to utilise additional Porsche Connect Online Services.

Alternatively, the PCM4 can also connect to a hotspot operated from the smartphone as a WiFi client. However, the telephone module installed in the PCM4 and associated external antenna ensure a faster, more stable mobile connection.



9\_95\_17




9\_96\_17

A precondition for using the services is a data plan for the SIM card inserted in PCM4 or the mobile phone.

### 9.13.12 TV tuner

The external TV tuner is available in 4 country versions (EU/RoW, China, Japan, Korea). The Japan version is equipped with an integral BCAS card reader. The mini BCAS card forms part of the as-delivered condition. (B-CAS = HDTV access protection in Japan).



9\_97\_17



### WiFi connections

Preferably via an additional SIM card, alternatively from a smartphone via the PCM4/hotspot as WiFi client.

### Internet access point

The WiFi hotspot is realised in the PCM4 via the LTE telephone module.

### Data services

A precondition for using the services is a data plan for the SIM card inserted in the PCM4 or the mobile phone.

### Hotspot

Public internet access point. It is possible to access the internet wirelessly via a hotspot.

### B-CAS (B-Conditional Access System)

HDTV access protection in Japan.

Receivers (ISDB/DTT-TV/DVD recorder).


Figure 9\_97\_17 The control units for the front-end electronics (BCM front) and ParkAssist are located next to the TV tuner.

## 718 Boxster/S

### Model Year 2017 (982)

#### Electrics and electronics

# 9



BOSE amplifier/digital

9\_98\_17

### 9.14 Sound systems

#### 9.14.1 Sound Package Plus (standard)

PCM4 is equipped with eight speakers and an integral amplifier with output of 150 watts as standard. The external analogue amplifier on the predecessor model has been omitted as a result of this output power. An integral digital sound processor for optimised adaptation of the sound pattern in the passenger compartment is also installed.

#### 9.14.2 BOSE® Surround Sound System

The BOSE amplifier is supplied in a country version. With the optional BOSE® Surround Sound System, the customer receives 12 fully active loudspeakers including a 100 watt active subwoofer integrated in the body and centre speaker. The amplifier has an output of 555 watts. The fully active system design enables the optimised adaptation of each individual speaker in the passenger compartment.



BOSE Surround Sound System

9\_99\_17



### 9.14.3 Burmester® High End Surround Sound System

The optional Burmester® High-End Surround Sound System offers the greatest performance with a total output of 821 watts and 12 independently controlled speakers, including a 300 watt active subwoofer integrated in the body. Analogue and digital filters were optimally defined for the specific installation positions.



Burmester components

9\_100\_17 Active subwoofer

9\_101\_17

The tweeters are ribbon-based air motion transformers (AMT) offering unmistakably fine, clear and undistorted high-frequency sound reproduction with excellent level stability. All loudspeaker chassis are perfectly coordinated with each other and deliver a natural, richly textured spatial sound, even at high volumes. The result is sound performance of the highest quality, specially adapted to the 718 Boxster MY17.



Installation positions of Burmester components

9\_102\_17

## 718 Boxster/S

### Model Year 2017 (982)

Electrics and electronics

9



Aha

9\_103\_17



Vodafone Cobra

9\_104\_17

## 9.15 Porsche Connect

### 9.15.1 Mobile Online Services/Aha

Mobile Online Services (MOS) were introduced in the Cayenne in 2012. These services include a smartphone application for iPhone or Android, which must be installed on the smartphone. Only free registration is required for this purpose. The necessary option must be available in the vehicle to be able to use the Mobile Online Services. Following successful connection of the smartphone to the PCM, "Aha" is available as the tuner source. The Aha app provides various services as radio programmes. The stations in the preset list in the smartphone app are available in the station list.

**Aha** functions at a glance:

- Internet radio stations: as audio stream (USA: > 2,000, Europe: > 1,100, of which Germany: > 500)
- Personalised web music (Slacker USA)
- Receives and reads out Facebook messages
- Receives and reads out Twitter messages
- Audio books
- Podcasts

### 9.15.2 Porsche Car Connect

In MY14, further online services were introduced in the Panamera; these were the Porsche Car Connect (PCC) services. The Porsche Car Connect smartphone app offers the option of establishing a wireless connection with the vehicle. This enables vehicle-specific information to be accessed directly via the smartphone and selected settings to be configured directly on the vehicle using the app.


## 718 Boxster/S Model Year 2017 (982)

### Electrics and electronics


9

Three in-vehicle versions are available:

- **Version 1** Porsche Car Connect (standard)
- **Version 2** Porsche Car Connect with PVTs Plus (Porsche Vehicle Tracking System Plus)
- **Version 3** E-mobility services (hybrid vehicles only)



Version 1 9\_105\_17



Version 2 9\_106\_17


With the 718 Boxster MY17, the previous services (Mobile Online Services and Porsche Car Connect) have now been replaced by the new Porsche Connect functionalities. The Aha radio app is replaced by "Porsche Connect". In parallel to Porsche Car Connect for vehicle-based functions, Porsche Connect provides new infotainment and navigation functions. The following new services have been introduced:

#### Backend server-based services

- Real-time traffic information (RTTI)
- Google Earth, Google Street View
- POI (Point of Interest) search

#### App-based services

- My Destinations
- Internet radio, personalised radio
- Flat-rate music services



Version 3 9\_107\_17

## 718 Boxster/S Model Year 2017 (982)

### Electrics and electronics

9

#### Internet radio

- Connection of the MIB to the online radio service “Radio.de” via the MIB multimedia app
- Huge selection of radio stations and independent regional radio stations available
- Digital reception is independent of the radio station coverage area

#### Real-time traffic information (RTTI)

- During active navigation, the latest traffic information and traffic disturbances are taken into account. Speed and flow information is displayed on the map and used for arrival time/journey duration calculations. Display is via colour-coding of the roads (traffic light system).
- **VICS (Vehicle Information and Communication System)** in Japan is an innovative information and communication system that receives real time information about traffic jams and traffic regulation.




Traffic flow

9\_110\_17



Flat-rate music streaming

9\_111\_17



Google Earth

9\_116\_17

#### Google Earth

- Navigation with Google Earth satellite maps in the map view
- Activation is via a Navigation setting in the Options menu or button in map

#### Google Street View

Google StreetView is an additional service to Google Earth that provides views of 360-degree panoramic images from a street perspective. (Google Earth must be activated in the PCM4/HMI).



Google Street View

9\_117\_17

### Personalised radio

- Personalised radio available based on the listening habits of the user (aupeo.de)
- Direct search possible in the vehicle (genres, popular stations, popular artists, etc.)
- Digital reception is independent of the radio station coverage area

### Flatrate music services

Access to flat-rate music services (Napster): Unlimited number of music tracks (tracks, albums, artists, playlists) available.

### Apple Car Play

Apple CarPlay® makes individual functions and apps on the iPhone available in the PCM.



Apple CarPlay displays on PCM4


9\_113\_17

### Use

Connection of an iPhone via the USB interface, CarPlay message appears.



The number of services can vary depending on the country!



9\_112\_17



## 718 Boxster/S

### Model Year 2017 (982)

Electrics and electronics

9

#### Prerequisites

From iPhone 5 or later, iOS 7.1 or higher, Siri and Apple CarPlay are activated on the iPhone in use.

#### Notes

While Apple CarPlay is being used, only the connected iPhone can be used to make phone calls. Only apps of the iPhone in use can be displayed that are supported by Apple CarPlay. For further information, see: [www.apple.com/ios/carplay](http://www.apple.com/ios/carplay).

The first time the iPhone is connected, the PCM queries whether the iPhone should only be used to play music like an iPod or whether Apple CarPlay® should be activated. Once the device is connected, ticking the checkbox ensures that the PCM saves the selection as default. Simply select the relevant icon in the home menu on the PCM to use Apple CarPlay®. In addition to the touchscreen, Apple CarPlay® can also be operated using certain hardkeys as well as the rotary pushbutton control. Above the voice control, pressing and holding the button on the steering wheel activates the Apple voice control "Siri". Just like on the iPhone. This function can be used to e.g. send, read aloud and answer text messages. Mobile phones connected to the PCM via Bluetooth (BT) are automatically disconnected. In the meantime, an inserted SIM cannot be used to make phone calls.

## 9.16 Abbreviations

	Deutsch	Englisch
ABT	Anzeige Bedien Teil	Display control unit/Touchscreen
ACC	Abstandsregeltempostat	Adaptive Cruise Control
AFS	Automatische FahrlichtSteuerung	Advanced frontlighting system
AGA	Schaltbare Abgasanlage	
AGM	AGM Batterie	Absorbent Glass Mat
ASD	Außenlaufendes SchiebeDach	Sliding roof
ALWR	Automatische Leucht Weiten Regulierung	Automatic headlamp levelling
AZV	AnhängerZugVorrichtung	Trailer hitch
B-CAS	HDTV-Zugangsschutz Japan	BS Conditional Access System
BCM	Karosseriesteuergerät	Body Control Module
BKE	Bedien Klima Einheit	Operating & AC unit
BMS	Batteriesensor	Battery Measurement Sensor
BT	Bluetooth Verbindung	BlueTooth
CAN	Zweidraht-Bus (CAN-high/CAN-low)	Controller Area Network
CDR	Infotainmentsystem	Infotainment system
CRC	Geschwindigkeitsregler	Cruise Control
DAB	Digitale hörbare Übertragung	Digital Audio Broadcast
DFI	Direkteinspritzer	Direct Fuel Injection
DMB	Digitale Mehrfachmedien Übertragung	Digital Multimedia Broadcast
DME	Digitale Motor Elektronik	Engine management system
DSRC	DSRC Kartenleser Japan	Dedicated Short Range Communication
DTMF	Dual Ton Mehrfrequenz	Dual Tone Multi Frequency
ELV	Elektrische Lenkungs Verriegelung	Electrical steering lock
ESD	Elektrostatische Entladung	Electro Static Discharge
ETC	Maut in Japan	Electronic Toll Collect
EPB	Elektrische Park Bremse	Electrical parking brake
EZS	Elektrisches Zünd Schloss	Electrical ignition switch
FBAS	Farbe Bild Ausstattung Synchronisation	Colour picture equipment synchronisation
FLA	FernLichtAssistent	High beam assist
GLW	GleitendeLeuchtWeite	Sliding light
HAL	HinterAchsenLenkung	Rear axle steering
HD	HochDruck	High pressure
HWE	HinterWagenElektronik	BCM rear
HMI	Mensch Maschine Schnittstelle	Human Machine Interface
HSB	HauptSicherungsBox/Stromverteiler	Main fusebox
IWT	Innerer WärmeTauscher	Internal heat exchanger
KBA	KameraBasierende Assistenzfunktionen	Camera based functions
KESSY	Schlüsselloser Zugang Fahrzeugstart	Keyless Entry Start System
KJS	Kühler Jalousie Steuergerät	Cooling flaps
KLMS	KombiLenkStockModul	Steering column switch module
LDW	Spurverlassenwarnung	Lane Departure Warning
LKS	Spurhalte Assistent	Lane Keeping Support

## 718 Boxster/S

### Model Year 2017 (982)

Electrics and electronics

9

	Deutsch	Englisch
<b>LEIMO</b>	<b>LE</b> istungs <b>MO</b> dul	Performance modul
<b>LIN</b>	Eindraht-Bus	<b>L</b> ocal <b>I</b> nterconnect <b>N</b> etwork
<b>LTE</b>	Langzeit Entwicklung	<b>L</b> ong <b>T</b> erm <b>E</b> volution
<b>LVDS</b>	Hochgeschwindigkeits-Schnittstelle zur Datenübertragung	<b>L</b> ow <b>V</b> oltage <b>D</b> ifferential <b>S</b> ignaling
<b>MBB</b>	<b>M</b> odularer <b>B</b> ackend <b>B</b> aukasten	Modulated backend construction kit
<b>MMX</b>	Mobile Internet und Multimedia	<b>M</b> ulti <b>M</b> edia <b>E</b> Xtension
<b>MPI</b>	Mehrfacheinspritzung	<b>M</b> ulti <b>P</b> oint <b>I</b> njection
<b>MOD</b>	<b>M</b> obile <b>O</b> nline <b>D</b> ienste	Mobile online services
<b>MOST</b>	Lichtwellenleiter Ringtopologie	<b>M</b> edia <b>O</b> riented <b>S</b> ystem <b>T</b> ransport
<b>MTP</b>	Medienübertragungsprotokoll	<b>M</b> edia <b>T</b> ransfer <b>P</b> rotocol
<b>ND</b>	<b>N</b> ieder <b>D</b> ruck	Low pressure
<b>PAS</b>	ACC Funktion	<b>P</b> orsche <b>A</b> ctive <b>S</b> afe
<b>PADM</b>	Aktive Aggregatelager	
<b>PASM</b>	El. geregeltes Dämpfungssystem	<b>P</b> orsche <b>A</b> ctive <b>S</b> uspension <b>M</b> anagement
<b>PCC</b>	Porsche Fahrzeug Kommunikation	<b>P</b> orsche <b>C</b> ar <b>C</b> onnect
<b>PCCB</b>	Porsche Keramik Bremse	<b>P</b> orsche <b>C</b> eramic <b>C</b> omposite <b>B</b> rake
<b>PCM</b>	Infotainmentsystem	<b>P</b> orsche <b>C</b> ommunication <b>M</b> anagement
<b>PDC</b>	ParkAssistent	<b>P</b> arc <b>D</b> istance <b>C</b> ontrol
<b>PDCC</b>	Fahrwerksystem zur Wankstabilisierung	<b>P</b> orsche <b>D</b> ynamic <b>C</b> hassis <b>C</b> ontrol
<b>PDK</b>	<b>P</b> orsche <b>D</b> oppel <b>K</b> upplungsgetriebe	Porsche double clutch transmission
<b>PDLS</b>	<b>P</b> orsche <b>D</b> ynamisches <b>L</b> icht <b>S</b> ystem	Porsche dynamic light system
<b>PDLS Plus</b>	<b>P</b> orsche <b>D</b> ynamisches <b>L</b> icht <b>S</b> ystem Plus	Porsche dynamic light system plus
<b>PLG</b>	Elektrische Heckklappe	<b>P</b> ower <b>L</b> ift <b>G</b> ate
<b>PSM</b>	<b>P</b> orsche <b>S</b> tabilitäts <b>M</b> anagement	Porsche stability management
<b>PTM</b>	Porsche Traktions Management	<b>P</b> orsche <b>T</b> raction <b>M</b> anagement
<b>PTV</b>	Porsche Drehmoment Regelung	<b>P</b> orsche <b>T</b> orque <b>V</b> ectoring
<b>PVTS</b>	Porsche Fahrzeugverfolgungssystem	<b>P</b> orsche <b>V</b> ehicle <b>T</b> racking <b>S</b> ystem
<b>RCC</b>	Audiosystem und Fahrzeuganbindung	
<b>RDK</b>	<b>R</b> eifen <b>D</b> ruck <b>K</b> ontrolle	Tyre pressure monitoring system
<b>RFK</b>	<b>R</b> ück <b>F</b> ahr <b>K</b> amera	Reverse camera
<b>RdW</b>	<b>R</b> est <b>d</b> er <b>W</b> elt Märkte	Rest of world markets
<b>RTTI</b>	Echtzeit Verkehrsinformation	<b>R</b> eal <b>T</b> ime <b>T</b> raffic <b>I</b> nformation
<b>SCR</b>	Ad Blue	<b>S</b> elective <b>C</b> atalytic <b>R</b> eduction
<b>SENT</b>		<b>S</b> ingle <b>E</b> dge <b>N</b> ibble <b>T</b> ransmission
<b>SMS</b>	Kurznachricht	<b>S</b> hort <b>M</b> essage <b>S</b> ervice
<b>SWA</b>	<b>S</b> pur <b>W</b> echsel <b>A</b> ssistent	Lane Change Assist
<b>SWaP</b>	<b>S</b> oft <b>W</b> are <b>a</b> ls <b>P</b> rodukt	Software as product
<b>USB</b>	Universelle Serielle Schnittstelle	<b>U</b> niversal <b>S</b> erial <b>B</b> us
<b>VICS</b>	Verkehrsfunksystem Japan	<b>V</b> ehicle <b>I</b> nformation and <b>C</b> ommunication <b>S</b> ystem
<b>VRLA</b>	Ventilgeregelte Blei-Säuren-Batterie	<b>V</b> alve <b>R</b> egulated <b>L</b> ead <b>A</b> cid
<b>VWE</b>	<b>V</b> order <b>W</b> agen <b>E</b> lektronik	BCM front
<b>VZA</b>	<b>V</b> erkehrs <b>Z</b> eichen <b>A</b> nzeige	Traffic sign view
<b>WLAN</b>	Drahtloses Netzwerk	<b>W</b> ireless <b>L</b> ocal <b>A</b> rea <b>N</b> etwork
<b>ZR</b>	<b>Z</b> entral <b>R</b> echner	Control process unit

## **Publisher's data**

Dr. Ing. h.c. F. Porsche  
Aktiengesellschaft  
Postfach 1108  
D-71634 Ludwigsburg

Department: After Sales Market Support  
Editorial work: Service Training (VAM3)

01/2016

Diagrams, descriptions and schematic drawings are provided for illustrative purposes only.

We accept no liability for the completeness of the content of this publication and for compliance with the valid legal provisions.

Right of technical modifications reserved.

### **Confidential!**

The texts and illustrations in this training material are intended solely for internal use within the Porsche dealer organisation. Approval from the Service Training department of Dr. Ing. h.c. F. Porsche AG shall always be required for any duplication or forwarding of this document to third parties, including the duplication or forwarding of extracts of the document.

© Copyright by Dr. Ing. h.c. F. Porsche AG

Printed in Germany

WASCxxxxxxxxx

